



Cat[®] 980M

Wheel Loader

The new 980M Wheel Loader has an ACERT™ engine equipped with a combination of proven electronic, fuel, and air components. Applying proven technologies systematically and strategically lets us meet your high expectations for productivity, fuel efficiency, reliability and service life. Deep system integration results in reduced emissions, improved performance and improved fuel economy without interrupting machine performance. Aggregate Handler and other optional configurations are available.**

RELIABILITY, PRODUCTIVITY AND FUEL EFFICIENCY

- 10% more fuel efficient than K Series*
- Up to 25% more efficient than H Series*

Linkage and Work Tools

- Performance Series buckets and range of work tools
- Coupler ready (option)

Engine and Aftertreatment Advancements

- Cat[®] engine with ACERT Technology
- Meets U.S. EPA Tier 3/EU Stage IIIA equivalent emission standards or U.S. EPA Tier 2/EU Stage II equivalent emissions standards, depending on emission standards of specific country.
- Productive economy mode

Transmission Advancements

- Powershift transmission with single clutch speed shifts and torque based down shifts
- Lock up clutch torque converter with lock-to-lock shifting
- Split flow oil system and multi-viscosity oil

Axle Advancements

- Caliper disk parking brake
- Limited slip differentials (option)

Next Generation Hydraulic Systems

- Next generation main valve
- Next generation ride control system with dual accumulators
- Full flow and kidney loop filtration
- Load-sensing hydraulics with simultaneous hydraulic functions
- 3rd function (option)

EASE OF OPERATION

Best-in-class Operator Environment

- Optimized all-around visibility
- E-H joystick steering (steering wheel optional)
- Touch screen multifunction color display with integrated controls and rearview camera
- Stair-like ingress and egress
- New wider door and increased glass area
- Seat-mounted fingertip electro-hydraulic implement controls
- Large convex rearview mirrors with integrated spot mirror
- Remote door opening (option)
- Automatic climate control
- Viscous cab mounts
- Low operator sound levels

Advanced Technology with Cat Connect

- Link technologies, like Product Link™ to monitor equipment and manage production using online VisionLink® software
- Payload technologies, like Cat Production Measurement (option) to measure payloads and optimize productivity
- Detect technologies, like the rear vision camera to keep people safe and help the operator work more productively

SERVICE ACCESS

- One-piece tilting hood with side and rear doors
- Centralized service centers for hydraulic and electrical components
- Windshield cleaning platform and harness tie-off

*Fuel efficiency is measured in mass of material moved per volume of fuel burned. Average efficiency improvement as tested and analyzed for an average composite cycle and stand configuration with variations per comparable model with and without economy mode active. Factors influence result variation such as, but not limited to, machine configuration, operator technique, machine application, climate, etc.

**Optional configuration and equipment may vary from region to region. Consult your Caterpillar representative for further details.



Cat® 980M Wheel Loader

Engine

Engine Model	Cat C13 ACERT	
Max Gross Power @ 1,800 rpm – SAE J1995	307 kW	412 hp
Max Gross Power @ 1,800 rpm – SAE J1995 (metric)	417 hp	
Max Power @ 1,800 rpm – ISO 14396	303 kW	406 hp
Max Power @ 1,800 rpm – ISO 14396 (metric)	412 hp	
Max Net Power @ 1,800 rpm – SAE J1349	278 kW	373 hp
Max Net Power @ 1,800 rpm – SAE J1349 (metric)	378 hp	
Max Net Power @ 1,800 rpm – ISO 9249	278 kW	373 hp
Max Net Power @ 1,800 rpm – ISO 9249 (metric)	378 hp	
Peak Gross Torque (1,300 rpm) – SAE J1995	2192 N·m	1,617 lbf-ft
Peak Gross Torque (1,300 rpm) – ISO 14396	2172 N·m	1,602 lbf-ft
Maximum Net Torque (1,100 rpm)	2040 N·m	1,505 lbf-ft
Displacement	12.5 L	763 in ³

Weights

Operating Weight 30 090 kg 66,337 lb

- Weight based on a machine configuration with Michelin 29.5R25 XLDD1 L4 radial tires, full fluids, operator, standard counterweight, cold start, roading fenders, Product Link, open differential axles, secondary steering, sound suppression, and a 5.4 m³ (7.1 yd³) GP bucket with BOCE.

Bucket Capacities

Bucket Range 4.2- 5.2-
12.2 m³ 16.0 yd³

Operating Specifications

Static Tipping Load – Full 40° Turn – with Tire Deflection 19 565 kg 43,133 lb

Static Tipping Load – Full 40° Turn – No Tire Deflection 20 796 kg 45,847 lb

Breakout Force 224 kN 50,357 lbf

- For a machine configuration as defined under “Weight.”
- Full compliance to ISO 143971:2007 Sections 1 thru 6.

Transmission

Forward 1	6.9 km/h	4.3 mph
Forward 2	13.3 km/h	8.3 mph
Forward 3	23.5 km/h	14.6 mph
Forward 4	39.5 km/h	24.5 mph
Reverse 1	7.8 km/h	4.8 mph
Reverse 2	15.2 km/h	9.4 mph
Reverse 3	26.9 km/h	16.7 mph
Reverse 4	39.5 km/h	24.5 mph

- Maximum travel speed in standard vehicle with empty bucket and standard L4 tires with 933 mm (37 in) roll radius.

Service Refill Capacities

Fuel Tank	426 L	112.5 gal
Cooling System	45 L	12 gal
Crankcase	37 L	9.8 gal
Transmission	77 L	20.3 gal
Differentials and Final Drives – Front	84 L	22 gal
Differentials and Final Drives – Rear	84 L	22 gal
Hydraulic Tank	153 L	40 gal

Hydraulic System

Implement System:

Maximum Pump Output (2,250 rpm)	449 L/min	119 gal/min
Maximum Operating Pressure	34 300 kPa	4,975 psi
Hydraulic Cycle Time – Total	10.1 Seconds	

Sound

With Cooling Fan Speed at Maximum Value:

Operator Sound Pressure Level (ISO 6396:2008)	75 dB(A)
Exterior Sound Power Level (ISO 6395:2008)	112 dB(A)
Exterior Sound Pressure Level (SAE J88:2013)	78 dB(A)*

*Distance of 15 m (49.2 ft), moving forward in second gear ratio.

Dimensions

	Standard Lift		High Lift	
	mm	ft"	mm	ft"
Height to Top of Hood	3110 mm	10'3"	3110 mm	10'3"
Height to Top of Exhaust Pipe	3746 mm	12'4"	3746 mm	12'4"
Height to Top of ROPS	3813 mm	12'7"	3813 mm	12'7"
Ground Clearance	453 mm	1'5"	453 mm	1'5"
Center Line of Rear Axle to Edge of Counterweight	2469 mm	8'2"	2469 mm	8'2"
Center Line of Rear Axle to Hitch	1900 mm	6'3"	1900 mm	6'3"
Wheelbase	3800 mm	12'6"	3800 mm	12'6"
Overall Length (without bucket)	7964 mm	26'2"	8164 mm	26'10"
Hinge-Pin Height at Maximum Lift	4539 mm	14'10"	4760 mm	15'7"
Hinge-Pin Height at Carry	621 mm	2'1"	678 mm	2'3"
Lift Arm Clearance at Maximum Lift	3795 mm	12'5"	4010 mm	13'1"
Rack Back at Maximum Lift	61 degrees		61 degrees	
Rack Back at Carry Height	48 degrees		48 degrees	
Rack Back at Ground	40 degrees		39 degrees	
Maximum Width over Tires	3296 mm	10'10"	3296 mm	10'10"
Tread Width	2440 mm	8'0"	2440 mm	8'0"

- All dimensions are approximate and based on Michelin 29.5R25 XLDD1 L4 radial tires.

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

AEXQ1939 (08-2016)

© 2016 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, “Caterpillar Yellow” and the “Power Edge” trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

VisionLink is a trademark of Trimble Navigation Limited, registered in the United States and in other countries.



Courtesy of MachineMarket