



HD+ 120 VV / HD+ 120 VO

HD+ 120 VV - Articulated tandem roller with two vibratory drums

HD+ 120 VO - Articulated tandem roller with vibratory and oscillating drum



- ▶ Ergonomic driver seat for perfect all-round visibility
- ▶ Driver seat including steering wheel and instrument panel can be rotated and moved
- ▶ Clear view of drum surface, its outer edge and working environment
- ▶ Hydrostatic all-wheel drive for excellent hill climbing ability



- ▶ Diesel engine with high power and low sound level
- ▶ Pressure sprinkler system with 2 water pumps; spray nozzles visible from driver seat
- ▶ Crab steering to increase working width

HD+ 120 W / HD+ 120 VO

HD+ 120 W - Articulated tandem roller with two vibratory drums
 HD+ 120 VO - Articulated tandem roller with vibratory and oscillating drum



		HD+ 120 W	HD+ 120 VO
Weights			
Operating weight with ROPS	kg	12610	12945
Operating weight with cab	kg	12850	13185
Operating weight, max.	kg	14010	14350
Axle load, front/rear	kg	6565/6285	6585/6600
Static linear load, front/rear	kg/cm	33,2/31,7	33,3/33,3
French classific., data/class		31,1/VT2	31,2/VT2
Machine dimensions			
Max. working width	mm	2150	2150
Lateral overhang, left/right	mm	50/50	50/50
Ground clearance, left/right	mm	880/880	880/880
Ground clearance, centre	mm	330	330
Turning radius, inside	mm	5285	5285
Drum thickness, front/rear	mm	19/19	19/17
Diesel engine			
Manufacturer		DEUTZ	DEUTZ
Type		TCD 2012 L04 2V	TCD 2012 L04 2V
Number of cylinders		4	4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300	100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300	100,0/134,0/2300
Emissions standard EU/USA		III A / Tier 3	III A / Tier 3
Fuel tank, capacity	L	180	180
Drive			
Hydrostatic drive, front/rear		Hydr. motor/hydr. motor	Hydr. motor/hydr. motor
Speed, working gear	km/h	0-6,0	0-6,0
Speed, transportation gear	km/h	0-12,0	0-12,0
Climbing ability, vibration on/off	%	30/35	30/35

Vibration system
 Hydrostatic drive, All-wheel-steered tandem roller with two vibratory drums

Vibration			
Vibration frequency, front, I/II	Hz	40/50	40/50
Vibration frequency, rear, I/II	Hz	40/50	
Amplitude, front, I/II	mm	0,88/0,49	0,88/0,49
Amplitude, rear, I/II	mm	0,88/0,49	
Centrifugal force, front, I/II	kN	159/138	159/138
Centrifugal force, rear, I/II	kN	159/138	
Oscillation			
Oscillation frequency, rear	Hz		36
Tangential amplitude, rear	mm		1,46
Oscillation force, rear	kN		205
Steering			
Steering, type		Articulated steering	Articulated steering
Steering, actuation		hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	°	30	30
Oscillation angle +/-	°	10	10
Sprinkler system			
Water sprinkler, type		Pressure	Pressure
Actuation, sprinkling		interval/manual	interval/manual
Water tank, capacity	L	1160	1160

Equipment
 Spring-mounted driver seat, Comfort seat can be swivelled and moved, Multifunction drive lever to right of seat, Amplitude, switchable: large/small, Vibration, switchable: front/rear/together, Indicator lights and emergency stop, Battery main switch, Triple oil filtering, Water level display, Speedometer, Access handles

Optional equipment
 HCQ asphalt compression meter, HCQ asphalt thermometer, Frequency regulator, switchable: front/rear/together, Crab steering to increase working width, ROPS panoramic cab, Heat/air conditioning with dehumidification, Dust-free ventilation, Interior lighting, Exterior and interior mirrors, Tachograph, Rotating beacon, Sound insulation, Edge pressing and cutting equipment, Radio, Back-up alarm, Second multifunction drive levers, Drum lighting, Cab: 4 headlights, All headlights available in Xenon, Fabric seat, Driver seat, back extension, Seat belt, Sunroof

Total length	L	5000	5000
Width	B	2145	2145
Total height	H	3050	3050
Wheel base	A	3600	3600
Roller drum width	X	1980/1980	1980/1980
Drum diameter	D	1400/1400	1400/1400
Height loading, min.	HI	2185	2185

