



Product Catalog

SPK60

Courtesy of Crane.Market

The Company



Jekko is a world leading manufacturer of minicranes with more than 45 years of experience in the lifting and handling sector. The company is headquartered in the province of **Treviso**, occupying a **17,000 sq. m.** industrial estate – 7,000 of which are indoors.

The entire range of **Jekko minicranes is exported and traded all over the world by a network of more than 30 authorised dealers**. Our products are engineered to meet our customers' specific requirements and are designed to **operate in narrow places where space is restricted**. Depending on the model, their **compact size** allows passage through a standard or double doorway. But their modest weight and slim dimensions come with no compromise to **lifting capacity or working range**, resulting in substantial

operational benefits both indoors and outdoors. Jekko offers a complete line of **models equipped with diesel engine, electric motor or battery pack** and a wide range of **attachments including hook or hydraulic jibs, grabber manipulators for pipes and beams, vacuum lifters for glass panes as well as lifting beams**. All tools are fully integrated with the functions and safety devices of the base machine.

Jekko has always invested in **R&D**, safety and compliance with all relevant regulations – in particular with the **EN 13000** standard – to **offer its customers innovative and safe products**. Jekko is a young business, supported by a professional technical department, reliable training and **after-sales services**, and a sales & marketing office covering all international markets.

	PRODUCTS
Jekko minicranes are safe and technologically advanced; payback on a minicrane is immediate in the case of a sale and achieved in the short term in the case of rental.	

	INTERNATIONAL NETWORK
Jekko is present in the five continents through its network of more than 30 authorised dealers.	

	AFTER-SALES SERVICE
Jekko's prompt and reliable after-sales operation offers an online service for spares and warranty management and a training department for technical courses.	



MADE IN ITALY

From design to assembly, as well as components and suppliers, all our products are 100% Made in Italy.



INNOVATION

Jekko products take innovation to the limit, with exhaustive research and engineering and a thorough understanding of market needs.

Our Products



MINICRANES

Six different telescopic mini crawler crane models with outriggers – designed for easy transport and ultimate versatility. These machines can work in all kinds of places – slopes, stairs, passageways and hard-to-reach places – and they are quick to set up.



TELE-CRAWLER CRANES

Jekko produces the only mini crawler crane on the market with an operator's cab and luffing capability thanks to its hydraulic articulated jib. It also has all the most advanced technological innovations that crane owners have come to expect: radio remote control, extendable tracks, option of diesel engine or electric motor, 3 T pick & carry capacity, hydraulic jib reaching 27.5 m and more than 50 configurations available.



JF SERIES ARTICULATED CRAWLER CRANES

This model, combining an articulated truck-loader crane on a self-propelled crawler chassis, offers a glimpse of the future of crawler cranes.

MINIPICKERS

Minipickers are our pick & carry self-propelled electric cranes powered by a battery and radio-remote controlled. They are well suited to working in warehouses or where access is difficult for other cranes, especially where heavy loads need to be carried through doorways. Minipickers can also be used with Jekko hydraulic manipulators or vacuum lifters for handling and positioning glazing or curtain walling.



VACUUM & TOOLS

Lifting and handling tools for glass panes and other materials. This family of products includes hydraulic or battery-powered manipulators, vacuum lifters for glass-pane handling, grabber manipulators for pipes and beams and other specific tools.




All our cranes are designed to operate in narrow places where space is restricted. Our ongoing R&D activity has brought these machines into many sectors of industry.

Sectors of application



Glass pane handling

Installation of glazing and curtain walling on buildings and skyscrapers, handling glass panes and non-porous materials using hydraulic manipulators and vacuum lifters integrated with our cranes.



Constructions & Building

All kinds of building work, from housing to civil engineering.



Industrial maintenance

Indoor and outdoor industrial maintenance: shopping malls, ships, museums, schools, hospitals, exhibition halls as well airports, sports grounds, roads, leisure parks, graveyards, houses, railways, etc...



Mining, oil, nuclear, chemical, drilling and military sectors

These specific fields demand the highest standards in terms of accuracy, light-weight tools and handiness: that's exactly what Jekko minicranes offer.



... and others

With its entrepreneurial flair, Jekko has introduced the mini crane concept to all kinds of niche applications, including cinema, advertising, product promotion, airspace, luxury, etc...



Our Strengths

1

4 SIDE INCLINATION MODES:

- ✓ 0°
- ✓ 0,7°
- ✓ 1,5°
- ✓ 3°

2

EXTENDABLE TRACKS

3

CRANE CABIN

- ✓ FOPS certificated
- ✓ Safety glazing
- ✓ Seat with lumbar support
- ✓ Air condition
- ✓ Radio FM
- ✓ Safety belt
- ✓ Panoramic roof

4

AUTOMATIC/SUGGESTED SELECTION

5

DIESEL ENGINE 53,7 KW TIER 4

6

COMFORTABLE PROPORTIONAL JOYSTICK WITH ALL CONTROLS ON THE THUMB

7

COURTESY OF CRANE.MARKET



Our Strengths

LMI LOAD MOMENT INDICATOR

- ✓ Displays all the information on the boom or any attachment position
- ✓ Displays weight of the load being lifted and the maximum safe working load capacity
- ✓ Prevents overloading and tipping by cutting out when safe limits are approached
- ✓ More than 60 configurations and load charts available



DIAGNOSTIC TROUBLE CODE (DTC)



REMOVABLE COUNTERWEIGHT



EASY TRANSPORT



OTHER FUNCTIONS

- ✓ Crane Carrier Interlock (CCI)
- ✓ Anti Two Block (A2B)
- ✓ Virtual Walls (VW)
- ✓ Two speed tracks (2ST)
- ✓ Plug & Play Attachment (PPA)



Configurations & Options



DIFFERENT ATTACHMENTS

Searcher hook
Luffing jib
Hydraulic jib (Up to 28 m)
Grabber Manipulator

ELECTRIC POWER PACK

HYDRAULIC EXTRA FUNCTIONS

VISUAL ANGLE INDICATOR (VAI)

RADIO REMOTE CONTROL

DOZER BLADE

PERSONALIZED COLOR

STEEL OR GEOGRIP TRACKS

INCLUDED IN THE STANDARD EQUIPMENT:

- ✓ 2 T swivel overhaul ball
- ✓ LED working light
- ✓ Tower lamp
- ✓ Extendable Tracks (EXT)

TOOL BOX

Courtesy of Crane.Market



SPK60



SPK60

6000 kg

3505 x 2320 x 2640 mm

max 27 m

max 18 m

The only mini crawler crane on the market with an operator's cab and luffing capability thanks to its hydraulic articulated jib – fully featured, advanced technology and more than 50 configurations.




Technical Information

Dimension	LxWxH	3505 x 2320 x 2640 mm
Track Ext.		3505 x 2920 mm

	Kg
SPK60	12200
/	1560
8T-D10	110
AUX	PP400-11D.V02 PP600-11D.V03
	140
JIB1501.3HL	650
JIB1501.FL	256
JIB3500GX	70
JIB300GR	245


SPK60	Diesel Engine	YANMAR 4TNV98CT-VPR	53.7 kW 73.0 Hp
-------	---------------	---------------------	--------------------

Speed		1.7/3.1 km/h
Gradiability		10°




Winch & Fall Stages

Main Winch	1500 kg 125 m - Ø 10 mm 30-55 m/min.
------------	--




Max. Capacity	Line	Metres
6000 kg	6	-20 m
6000 kg	5	-23 m
6000 kg	4	-28 m
4500 kg	3	-38 m
3000 kg	2	-58 m
1500 kg	1	-116 m

Load Chart




Dimensions



Tools Configurations

Crane Options



A2B BPI CCI DTC EXT GSC LMI P&C PPA SCI TH VW RCD 2SW 2ST

JIB3500GX

3500 kg
max 1330 kg @ 20.5 m
max 150 kg @ 18.5 m

JIB1501.3HL

1500 kg
max 490 kg @ 26 m
max 150 kg @ 18.5 m

JIB1501.1FL

1500 kg
max 700 kg @ 26 m
max 200 kg @ 14 m

JIB300GR

300 kg
max 300 kg @ 16 m
max 300 kg @ 11 m



S Symbols

	Extendable tracks Cingoli estensibili Ausdehnbare Raupen Cíngulos extensibles Chenilles extensibles		Electrical system Impianto elettrico Elektrische Anlage Sistema eléctrico Circuit électrique		Boom Slewing Rotazione braccio Auslegerdrehung Giro Rotation rallonge		Max reach Sbraccio massimo Max. Reichweite Alcance máximo Extension maximale du bras		Gradeability Pendenza superabile Steigfähigkeit Grado de inclinación Aptitude en pente		Main winch Argano principale Haupthubwerk Huinch principal Treibt principal		Tilting angle Angolo di inclinazione Auslegerverstellwinkel Ángulo de inclinación Angle flèche		Slewing Rotazione Drehwerk Rotación Rotación		Liquid cooling Raffreddamento liquido Flüssigkeitskühlung Enfriamiento del líquido Refridgement liquide						
	Dimensions Dimensioni Abmessungen Dimensiones Dimensions		Weight Peso Gewicht Peso total Poids		Travel speed Velocità di traslazione Fahrgeschwindigkeit Velocidad de desplazamiento Vitesse de déplacement		Auxiliary power pack Elettropompa ausiliaria Zusatzpumpe Electrobomba auxiliar Électropompe auxiliaire		Man basket SWL Capacità cestello Korblast Capacidad carretilla Capacité nacelle		Basket rotation Rotazione Cestello Korb schwenkung Electrobomba auxiliar Électropompe auxiliaire		Max height Altezza massima Max. Höhe Altura máxima Hauteur maximale		Max outrigger load Stabilizzatori Abstützungen Estabilizadores Stabilisateurs		Main winch Jib – prolunga Auslegerverlängerung Jib prolongación Flèche		Rotation angle Angolo di rotazione Drehwinkel Ángulo de rotación Ángulo de rotación		Slewing Rotazione Drehwerk Rotación Rotación		Building site use Utilizzo in cantiere Gebrauch auf Baustelle Utilización en el sitio Utilisation sur le site
	Counterweight Contrappeso Gegengewicht Contrapeso Contrepoids		Boom lifting Elevazione braccio Wippwerk Elevación de pluma Levage		Max working height Massima altezza di lavoro Max. Arbeitshöhe Altura máxima Hauteur max. de travail		Number of pads Numero di ventose Capacità cestello Número de ventosas Capacité nacelle		Opened lifting beam Bilanciere aperto Geöffnete Traverse Balgancine de carga abierto Balancier ouvert		Opened lifting beam Bilanciere aperto Geöffnete Traverse Balgancine de carga abierto Balancier ouvert		Max track loading Pressione al suolo Boden druck Presión de apoyo Pression au sol		Max track loading Pressione al suolo Boden druck Presión de apoyo Pression au sol		Main winch Jib – prolunga Auslegerverlängerung Jib prolongación Flèche		Rotation angle Angolo di rotazione Drehwinkel Ángulo de rotación Ángulo de rotación		Slewing angle Angolo di rotazione Schwenkwinkel Ángulo de rotación Angle de rotation		Manipulator Manipolatore Manipulator Manipulador Manipulateur
	Boom telescoping Lunghezza braccio Teleskopierlänge Brazo telescopico Télescopage flèche		Max working radius Massimo raggio di lavoro Max. Reichweite Rayo máximo de trabajo Rayon max. de travail		Factory use Utilizzo in fabbrica Gebrauch in Werkhalle Utilización en la fábrica Utilisation dans l' usine		Pad diameter Diametro ventosa Saugtellerrundmesser Diámetro ventosa Diamètre ventouse		Closed lifting beam Bilanciere chiuso Geschlossen Traverse Balgancine de carga cerrado Balancier fermé		Closed lifting beam Bilanciere chiuso Geschlossen Traverse Balgancine de carga cerrado Balancier fermé		Maximum SWL Portata massima Max. Tragfähigkeit Carga máxima Portée max.		Rope length Lunghezza fune Seilänge Longitud de la cuerda Longueur câble		Vertical lifting Sollevamento verticale Vertikaler Hub Elevación vertical Elevation verticale		Vertical lifting Sollevamento orizzontale Horizontaler Hub Elevación horizontal Elevation horizontale		Stabilization area Area di stabilizzazione Abstützung Área de estabilización Zone de stabilisation		
	Extendable tracks Cingoli estensibili Ausdehnbare Raupen Cíngulos extensibles Chenilles extensibles		Stability Control Indicator GSC		Tilting Head TH		Boom Pressure Indicator BPI		Two Speed Tracks 2ST		Load Moment Indicator LMI		Plug & Play Attachment PPA		Radio Control Display RCD		Two Speed Winch 2SW		Diagnostic Trouble Code DTC		Virtual Wall VW		
	Counterweight Contrappeso Gegengewicht Contrapeso Contrepoids		Stability Control Indicator SCI		Tilting Head TH		Boom Pressure Indicator BPI		Two Speed Tracks 2ST		Load Moment Indicator LMI		Plug & Play Attachment PPA		Radio Control Display RCD		Two Speed Winch 2SW		Diagnostic Trouble Code DTC		Virtual Wall VW		

A Acronyms

A2B	Anti Two Block	GSC	Geometrical Stability Control	TH	Tilting Head	BPI	Boom Pressure Indicator	PPA	Plug & Play Attachment	2SW	Two Speed Winch	DTC	Diagnostic Trouble Code	VW	Virtual Wall
EXT	Extendable Tracks	SCI	Stability Control Indicator	2ST	Two Speed Tracks	LMI	Load Moment Indicator	RCD	Radio Control Display	CCI	Crane-Carrier Interlock	P&C	Pick & Carry		

Notes: All specifications and features herein described can be changed without prior advice. All indicated data are indicative only and are not binding as crane performs differently depending on its use.

Note: Tutte le caratteristiche e le specifiche descritte possono essere soggette a variazioni senza preavviso. Tutti i dati riportati sono forniti a puro titolo informativo e non sono impegnativi dal momento che le prestazioni della macchina variano in funzione dell'utilizzo.

Hinweise: Unangekündigte Änderungen sämtlicher Eigenschaften und Daten sind möglich. Alle Angaben sind Richtwerte und nicht verbindlich da die Leistungen der Vorrichtung von deren Einsatz abhängen.

Notas: Todas las características y las especificaciones aquí indicadas pueden ser sujetas a variaciones sin aviso. Se dan todos los datos aquí indicados como simples informaciones. No se consideran como vinculantes, dado que las prestaciones del maquinario pueden variar.


Notes: Toutes les caractéristiques et les spécifications descriptives peuvent être sujet à variation sans préavis. Tout les données rapportés sont fourni à titre informatif et ne sont pas engager au moment que la prestation de la machine change en fonction de l'emploi.

Web



www.jekko.it

Visit **jekko.it** to keep in contact with us, discover all the latest news and find out technical details of all our products.





Jekko srl

Via Campadone, 1 - 31014 Colle Umberto (TV) Italy
info@jekko.it - www.jekko.it