



DIRECT MOUNT SERIES

1233 TRAIN



DOUBLE CAPACITY



The multipurpose K-Tec™ 1233 Train is an efficient worker in any soil condition with productive cycles. The 1233 Train provides a tandem heaped capacity of 66 cubic yards.

1233 TRAIN SPECIFICATIONS

General Specifications	Standard	Metric
Heaped Capacity (ISO)	66 Cubic Yards	50.46 Cubic Metres
Struck Capacity	39.4 Cubic Yards	30.12 Cubic Metres
Max Loading Rating	160,000 lbs	72,574 kgs
Bucket Dimensions	12' W x 4' 3" H x 12' 10" L	3.66m W x 1.29m H x 3.91m L
Cutting Width	14'	4.27m
Cutting Edge	3-Piece Blade	3-Piece Blade
Gate Opening	80"	2.03m
Rack Height (Tiltable)	4'	1.22m
Gate Cylinders	5" x 26"	127mm x 660mm
Lift Cylinders	5.5" x 32"	140mm x 813mm
Ejector Cylinders	5.5" x 76"	140mm x 1,930mm
Transport Cutting Edge Clearance	28"	0.71m
Combined Overall Length	69' 1"	21.1m
Hitch Pin To Rear Axle Length	31' 5"	9.55m
Wrap Around Mud Scrapers	Standard	Standard
Rear Scraper Structural Package	Gooseneck Hitchpole	
Lead Scraper Structural & Hydraulic Package	Rear C-Frame Hooks, Valve, Lines + Electrical	
Radial Tires (4) - Standard on Lead Scraper	26.5 R25	26.5 R25
Radial Tires (4) - Standard on Rear Scraper	23.5 R25	23.5 R25


K-Tec Scraper Features



Optional Upgrades


Radial Tires (4) On Rear Scraper	26.5 R25
Brake System	4 caliper disc brakes per unit

Recommended Power Units



Agricultural Tractors

450HP +/-331 KW +



Construction Tractors

Transportation Measures	Standard	Metric
Overall Width	14'	4.27m
Overall Height	10'	3.04m
Overall Length	38' 5", 36' 8"	11.71m, 11.18m
Shipping Weight	37,750 lbs, 38,666 lbs	17,123 kgs, 17,538 kgs

Specifications are subject to change without notice.

Gallery

Topsoil + Clay / Manitoba, Canada



Sand + Clay / Colorado, USA



Clay / Manitoba, Canada



Topsoil / North Dakota, USA



Topsoil, Clay / Manitoba, Canada



Sand / North Dakota, USA

