





The K-Tec[™] 1243 ADT is designed for self-loading with a 40-ton, 450+ horsepower rock truck. The 1243 ADT utilizes K-Tec's proprietary gooseneck hitching system, and has a PSI strength which is significantly greater than many competing scrapers. It features fast hydraulics, a smooth ride, and joystick scraper control.



1243 ADT SPECIFICATIONS

General Specifications	Standard	Metric	IIII Gallery
Heaped Capacity (ISO)	43 Cubic Yards	32.9 Cubic Metres	
Struck Capacity	25.7 Cubic Yards	19.6 Cubic Metres	Gravel / Tex
Max Loading Rating	103,200 lbs	46,810 kgs	
Bucket Dimensions	12' W x 5" H x 12' 7" L	3.66m W x 1.52m H x 3.87m L	
Cutting Width	14'	4.27m	1000
Cutting Edge	3-Piece Blade	3-Piece Blade	
Gate Opening	74.3"	1.88m	The second
Rack Height (Tiltable)	3'9"	1.14m	Topsoil / Ca
Gate Cylinders	6" x 26.25"	152mm x 667mm	
Lift Cylinders	6" x 38"	152mm x 965mm	a second
Ejector Cylinder	5.5" x 76"	140mm x 1,930mm	
Transport Cutting Edge Clearance	29"	0.74m	OPEOC
Ball To Rear Axle Length	31'4"	9.55m	
Gate Extension	Standard	Standard	Clay / Winr
Roller-Push Block	Standard	Standard	
Radial Tires (4)	26.5 R25	26.5 R25	
			S. THERE & REEL





Clay / Winnipeg, MB





Topsoil / California, USA



Sand / Macomb, IL



Topsoil / Rosenort, MB




-	⊚K-Tec Scrap	per Features				
	Sand Create Points	Resile To	ADD TUCK 2005 TUCK 2006 TUCK	Contraction of the second seco	A LONG	

Optional Upgrades Radial Tires (4)

Brake System

RTIFLE

- Hydraulic Filter System Truck Fender System
- Truck Chassis Catwalk Sytem
- ©Recommended Power Units



29.5 R25 29.5 R29 24.00 R35

8 caliper disc brakes

Easy access steps and platform

Prevents cross-contamination between scraper $\&\ truck$

Protects truck from material flinging from tires

Transportation Measures	Standard	Metric	
Overall Width	14'	4.25m	
Overall Height	9' 5"	2.87m	
Overall Length	40' 3"	12.28m	
Shipping Weight	50,160 lbs	22,752 kgs	

Specifications are subject to change without notice.