

FLEX

XL SERIES



LAND LEVELING (EASILY) TRANSPORTED

Our heavy duty box scrapers thrive in construction and agriculture industries. Designed for maintaining haul roads, precision leveling and field drainage; the Flex XL models enable the folding back of the hitchpole and foldable wheels for legal road width to transport the leveler between jobsites.



2822 FLEX SPECIFICATIONS



General Specifications	Standard	Metric
Bucket Dimensions	28' W x 5.1' H x 4.6' L	8.5m W x 1.55m H x 1.4m L
Capacity	22.8 Cubic Yards	17.4 Cubic Metres
Cutting Width	28'	8.53m
Single Simplistic Tilt	Standard	Standard
Depth Level Gauge	Standard	Standard
LED Light Package	Standard	Standard
Mechanical Slopometer No.1	Standard	Standard

Optional Upgrades

Rear Hitch To efficiently tow implements.

Blade Configurations

8" (203mm) Curved Grader Blade


Straight Flat Cutting Edge

Serrated Cutting Edge

K-Tec Land Leveler Features



Recommended Power Units



Agricultural Tractors 450HP +/-335 KW +

Transportation Measures	Standard	Metric
Overall Width	28.25'	8.6m
Overall Length	31.25'	9.52m
Folded Transportation Dimensions	10' 5" W x 10' 7" H x 35' L	3.1m W x 3.2m H x 10.6m L
Shipping Weight	18,780 lbs	8,518 kgs

* Specifications are subject to change without notice.

Gallery

28 Foot Cutting Width



Foldable Wheels For Transport



Topsoil / Manitoba, Canada



Topsoil / Arkansas, USA

