

# KOMATSU®

# PC210LC-11

Tier 4 Final Engine

## HYDRAULIC EXCAVATOR



Photos may include optional equipment.

### NET HORSEPOWER

165 HP @ 2000 rpm  
123 kW @ 2000 rpm

### OPERATING WEIGHT

51,397–53,882 lb  
23313–24440 kg

### BUCKET CAPACITY

0.66–1.57 yd<sup>3</sup>  
0.50–1.20 m<sup>3</sup>

# PC210LC



# WALK-AROUND

PC210LC-11



Photos may include optional equipment.

## NET HORSEPOWER

165 HP @ 2000 rpm  
123 kW @ 2000 rpm

## OPERATING WEIGHT

51,397–53,882 lb  
23313–24440 kg

## BUCKET CAPACITY

0.66–1.57 yd<sup>3</sup>  
0.50–1.20 m<sup>3</sup>



## PERFORMANCE & FUEL ECONOMY

New engine with up to 4% more horsepower and up to 6% better fuel consumption than the PC210LC-10.



A powerful **Komatsu SAA6D107E-3 engine** provides a net output of 123 kW **165 HP**. This engine is EPA Tier 4 Final emissions certified.

**Variable Geometry Turbocharger (VGT)** uses a hydraulic actuator to provide optimum air flow under all speed and load conditions.

**Komatsu Diesel Particulate Filter (KDPF) and Selective Catalytic Reduction (SCR) system** reduce particulate matter and NOx while providing automatic regeneration that does not interfere with daily operation.

**Komatsu's Closed-center Load Sensing System (CLSS)** provides quick response and smooth operation to maximize productivity.

**Enhanced working modes** are designed to match engine speed, pump delivery, and system pressure to the application.

**KOMTRAX®** equipped machines can send location, service meter reading and operation maps to a secure website or smart phone utilizing wireless technology. Machines also relay error codes, cautions, maintenance items, fuel & Diesel Exhaust Fluid (DEF) levels, and much more.

### Large LCD color monitor panel:

- 7" high resolution screen
- Provides "Eco-Guidance" for fuel efficient operation
- Enhanced attachment control

### Rearview monitoring system (standard)

**Equipment Management Monitoring System (EMMS)** continuously monitors machine operation and vital systems to identify machine issues and assist with troubleshooting.

**Triple labyrinth final drive cover** helps prevent mud packing.

### Enhanced working environment

- High back, heated air suspension operator seat with new adjustable arm rests
- Integrated ROPS cab design
- Cab meets ISO Level 1 Operator Protective Guard (OPG) top guard
- Aux jack and (2) 12V power outlets

**Wide access service doors** provide easy access for ground level maintenance.

**Guardrails (standard)** on both sides provide more convenient access to the upper structure.

**Battery disconnect switch** allows a technician to disconnect the power supply before servicing the machine.

### Komatsu designed and manufactured components

**Swing out cooler design** provides easy access to service and clean the cooler assembly.

**Komatsu Auto Idle Shutdown** helps reduce idle time and operating costs.

**Operator Identification System** can track machine operation for more than 100 operators.



# PERFORMANCE FEATURES

## KOMATSU NEW ENGINE TECHNOLOGIES


### New Tier 4 Final Engine

The Komatsu SAA6D107E-3 engine is EPA Tier 4 Final emissions certified and provides exceptional performance while reducing fuel consumption. Based on Komatsu proprietary technologies developed over many years, this new diesel engine reduces nitrogen oxides (NOx) by more than 80% when compared to Tier 4 interim levels. Through the in-house development and production of engines, electronics, and hydraulic components, Komatsu has achieved great advancements in technology, providing high levels of performance and efficiency in virtually all applications.

### Technologies Applied to New Engine



#### Heavy-duty aftertreatment system

This new system combines a Komatsu Diesel Particulate Filter (KDPF) and Selective Catalytic Reduction (SCR). The SCR NOx reduction system injects the correct amount of Diesel Exhaust Fluid (DEF) at the proper rate, thereby decomposing NOx into non-toxic water vapor (H<sub>2</sub>O) and nitrogen gas (N<sub>2</sub>).



#### Heavy-duty cooled Exhaust Gas Recirculation (EGR) system

The system recirculates a portion of exhaust gas into the air intake and lowers combustion temperatures, thereby reducing NOx emissions. EGR gas flow has been decreased for Tier 4 Final with the addition of SCR technology. The system achieves a dynamic reduction of NOx, while helping reduce fuel consumption below Tier 4 Interim levels.




#### Advanced Electronic Control System

The electronic control system performs high-speed processing of all signals from sensors installed in the vehicle providing total control of equipment in all conditions of use. Engine condition information is displayed via an on-board network to the monitor inside the cab, providing necessary information to the operator. Additionally, managing the information via KOMTRAX helps customers keep up with required maintenance.

#### Variable Geometry Turbocharger (VGT) system

The VGT system features proven Komatsu design hydraulic technology for variable control of air-flow and supplies optimal air according to load conditions. The upgraded version provides better exhaust temperature management.






### Komatsu Auto Idle Shutdown

Komatsu auto idle shutdown automatically shuts the engine down after idling for a set period of time to reduce unnecessary fuel consumption and exhaust emissions. The countdown to engine shutdown can be easily programmed from 5 to 60 minutes.



### Heavy-Duty High-Pressure Common Rail (HPCR) Fuel Injection System

The system is designed to achieve an optimal injection of high-pressure fuel by means of computerized control, providing close to complete combustion to reduce PM emissions. While this technology is already used in current engines, the new system uses high pressure injection, thereby reducing both PM emissions and fuel consumption over the entire range of engine operating conditions. The Tier 4 Final engine has advanced fuel injection timing for reduced fuel consumption and lower soot levels.



### Fuel Consumption

**Reduced by up to 6%**

(vs PC210LC-10 Based on typical work pattern  
Collected via KOMTRAX)

This fuel consumption data is the result of using a prototype machine.



# PERFORMANCE FEATURES

## Increased Work Efficiency

### Powerful digging force

With the one-touch Power Max. function digging force is increased. (8.5 seconds of operation)

#### Maximum arm crowd force (ISO)

**101 kN(10.3t) ➔ 108 kN(11.0t) 7% UP**  
(with Power Max.)

#### Maximum bucket digging force (ISO)

**138 kN(14.1t) ➔ 149 kN(15.2t) 8% UP**  
(with Power Max.)

Measured with Power Max. function, 3045 mm arm and ISO rating



## Large Displacement High Efficiency Pump


Large displacement hydraulic implement pumps provide high flow output at lower engine RPM as well as operation at the most efficient engine speed.



## Working Mode Selection

The PC210LC-11 excavator is equipped with six working modes (P, E, L, B, ATT/P and ATT/E). Each mode is designed to match engine speed, pump flow, and system pressure to the application. The PC210LC-11 features an attachment mode (ATT/E) that allows operators to run attachments while in Economy mode.

Working Mode	Application	Advantage
<b>P</b>	Power mode	<ul style="list-style-type: none"> <li>•Maximum production/power</li> <li>•Fast cycle times</li> </ul>
<b>E</b>	Economy mode	<ul style="list-style-type: none"> <li>•Good cycle times</li> <li>•Better fuel economy</li> </ul>
<b>L</b>	Lifting mode	<ul style="list-style-type: none"> <li>•Increases hydraulic pressure</li> </ul>
<b>B</b>	Breaker mode	<ul style="list-style-type: none"> <li>•Optimum engine rpm, hydraulic flow</li> </ul>
<b>ATT/P</b>	Attachment Power mode	<ul style="list-style-type: none"> <li>•Optimum engine rpm, hydraulic flow, 2-way</li> <li>•Power mode</li> </ul>
<b>ATT/E</b>	Attachment Economy mode	<ul style="list-style-type: none"> <li>•Optimum engine rpm, hydraulic flow, 2-way</li> <li>•Economy mode</li> </ul>



## High Rigidity Work Equipment

Booms and arms are constructed with thick plates of high tensile strength steel. In addition, these structures are designed with large cross sectional areas and large one piece castings in the boom foot, the boom tip, and the arm tip. The result is work equipment that exhibits long term durability and high resistance to bending and torsional stress. A standard HD boom design provides increased strength and reliability.



PC210LC-11



# WORKING ENVIRONMENT



# WORKING ENVIRONMENT



PG210LG-11

## Comfortable Working Space

### Wide spacious cab

The wide spacious cab includes a heated air suspension seat with reclining backrest. The seat height and position are easily adjusted using a pull-up lever. The armrest position is easily adjusted together with the console.

### Arm rest with simple height adjustment function

A knob and plunger on the armrests allows easy height adjustment without the use of tools.



### Low vibration with cab damper mounting

### Automatic climate control

### Pressurized cab

### Auxiliary input jack

Connecting a regular audio device to the auxiliary jack allows the operator to hear the sound from the stereo speakers installed in the cab.



## Standard Equipment


Sliding window glass (left side)



Radio, ashtray



Remote intermittent wiper with windshield washer



Cigarette lighter



Opening & closing skylight




Magazine box & cup holder



Defroster (conform to the ISO standard)



One-touch storable front window lower glass





**LARGE HIGH RESOLUTION LCD MONITOR**



**New Monitor Panel Interface Design**

An updated large high resolution LCD color monitor enables accurate and smooth work. The interface has been redesigned to display key machine information in a new user friendly interface. A rear view camera and an DEF level gauge display have been added to the default main screen. The interface has a function that enables the main screen mode to be switched, thus enabling the optimum screen information for the particular work situation to be displayed.

**Indicators**


- 1 Auto-decelerator
- 2 Working mode
- 3 Travel speed
- 4 Ecology gauge
- 5 Camera display
- 6 Engine coolant temperature gauge
- 7 Hydraulic oil temperature gauge
- 8 Fuel gauge
- 9 DEF level gauge
- 10 Service meter, clock
- 11 Fuel consumption gauge
- 12 Guidance icon
- 13 Function switches
- 14 Camera direction display
- 15 DEF level caution lamp

**Basic operation switches**

- 1 Auto-decelerator
- 2 Working mode selector
- 3 Travel speed selector
- 4 Buzzer cancel
- 5 Wiper
- 6 Window washer
- 7 Auto climate controls

**Switchable Display Modes**

The main screen display mode can be changed by pressing the F3 key.



**Visual user menu**

Pressing the F6 key on the main screen displays the user menu screen. The menus are grouped for each function, and use easy-to-understand icons which enable the machine to be operated easily.



- 1 Energy saving guidance
- 2 Machine settings
- 3 Aftertreatment devices regeneration
- 4 SCR information
- 5 Maintenance
- 6 Monitor setting
- 7 Message check

# WORKING ENVIRONMENT

## Support Efficiency Improvement

### Ecology guidance

While the machine is operating, ecology guidance pops up on the monitor screen to notify the operator of the status of the machine in real time.

### Ecology gauge & fuel consumption gauge


The monitor screen is provided with an ecology gauge and also a fuel consumption gauge which is displayed continuously. In addition, the operator can set any desired target value of fuel consumption (within the range of the green display), enabling the machine to be operated with better fuel economy.



Ecology gauge      Fuel consumption gauge  
Ecology guidance

### Operation record, fuel consumption history, and ecology guidance record


The ecology guidance menu enables the operator to check the operation record, fuel consumption history and ecology guidance record from the ecology guidance menu, with a single touch.



Operation record



Fuel consumption history



Ecology guidance record

## Operator Identification Function

An operator identification ID can be set up for each operator, and used to manage operation information of individual machines using KOMTRAX data. Data sent from KOMTRAX can be used to analyze operation status by operator as well as by machine.




PC210LC-11



# MAINTENANCE FEATURES

## Centralized engine check points

Locations of the engine oil check and filters are integrated into one side to allow easy maintenance and service.




Engine oil filter

High efficiency fuel filter

Fuel pre-filter (with water separator)

## Battery disconnect switch

A standard battery disconnect switch allows a technician to disconnect the power supply and lock out before servicing the machine.



## Easy to access air conditioner filter

## Washable cab floor mat

## Sloping track frame

## Utility space

## Easy cleaning of coolers


Side by side panel engine and hydraulic oil coolers simplify maintenance.

## Fuel pre-filter with water separator

## Electric fuel priming pump

## High efficiency fuel filter with water separator

## Easy access to engine oil filter, engine oil, drain valve, fuel drain valve and water separator drain valve



# MAINTENANCE FEATURES

## Long-life oils, filters

High performance filters are used in the hydraulic circuit and engine. By increasing the oil and filter replacement intervals, maintenance costs can be significantly reduced.



Hydraulic oil filter  
(Ecology-white element)

Engine oil & Engine oil filter	every 500 hours
Hydraulic oil	every 5000 hours
Hydraulic oil filter	every 1000 hours
DEF pump filter	every 2000 hours

## Large capacity air cleaner

Large capacity air cleaner is comparable to that of larger machines. The larger air cleaner can extend air cleaner life during long-term operation and helps prevent early clogging, and resulting power loss. A radial seal design is used for reliability.

## Diesel Exhaust Fluid (DEF) tank

A large tank volume extends operating time before refilling and is installed on the right front stairway for ease of access.



## Maintenance Information

### "Maintenance time caution lamp" display

When the remaining time to maintenance becomes less than 30 hours\*, a maintenance time monitor appears. Pressing the F6 key switches the monitor to the maintenance screen.

\* : The setting can be changed within the range between 10 and 200 hours.



Maintenance screen

### Manual Stationary Regeneration

Under most conditions, active regeneration will occur automatically with no effect on machine operation. In case the operator needs to disable active regeneration or initiate a manual stationary regeneration, this can be easily accomplished through the monitor panel. A soot level indicator is displayed to show how much soot is trapped in the KDPF.

Soot level indicator



Aftertreatment device regeneration screen

### Supports the DEF level and refill timing

The DEF level gauge is displayed continuously on the right side of the monitor screen. In addition, when DEF level is low, DEF low level guidance messages appear in pop up displays to inform the operator in real time.




DEF level gauge

DEF low level guidance

### DT-type connectors

Sealed DT-type electrical connectors provide high reliability, water and dust resistance.





# GENERAL FEATURES

## ROPS CAB STRUCTURE


### ROPS Cab (ISO 12117-2)

The machine is equipped with a ROPS cab that conforms to ISO 12117-2 for excavators as standard equipment. It also satisfies the requirements for Level 1 Operator Protective Guard (OPG) and top guard (ISO 10262).




## Rear View Monitoring System

A new rear view monitoring system display has a rear view camera image that is continuously displayed together with the gauges and important vehicle information. This enables the operator to carry out work while easily checking the surrounding area.



## Low Vibration with Viscous Cab Mounts

The PC210LC-11 uses viscous mounts for the cab that incorporate a longer stroke and the addition of a spring. The cab damper mounting combined with a high rigidity deck reduces vibration at the operator's seat.



## General Features

**Secondary engine shut down switch** at base of seat to shutdown the engine.



**Lock lever**

**Seat belt retractable**

**Tempered & tinted glass**

**Large mirrors**

**Slip-resistant plates**

**Thermal and fan guards**

**Pump/engine room partition**

**Travel alarm**

**Large cab entrance step**

**Left and right side hand rails**



**Seat belt caution indicator**



# KOMATSU PARTS & SERVICE SUPPORT



## Every new Komatsu Tier 4 Final construction machine is covered.

The Komatsu CARE program covers all new Komatsu Tier 4 Final construction equipment, whether rented, leased or purchased. For the first 3 years or 2,000 hours, whichever occurs first, you'll receive:

- Regular service at 500, 1,000, 1,500 and 2,000-hr. intervals
- DEF tank breather element replacement at 1,000 hours
- DEF and CCV filters replacement at 2,000 hours
- 50-point inspection by factory-trained technician at each scheduled interval
- Technician labor
- Fluids, oils, coolant, filters, SCR screen, tank breather and parts
- Technician travel to and from your equipment location

Plus two complimentary scheduled KDPF exchanges and SCR system service for 5 years-no hours limits.\*

Service will be performed by a Komatsu Distributor and only Komatsu genuine fluids and filters will be used.

Komatsu CARE® services are available from every Komatsu Distributor in the U.S. and Canada.



## Komatsu CARE® – Extended Coverage

- Extended Coverage can provide peace of mind by protecting customers from unplanned expenses that effect cash flow
- Purchasing extended coverage locks-in the cost of covered parts and labor for the coverage period and helps turn these into fixed costs



\* Some exclusions apply. Please contact your Komatsu distributor for specific program details.



## Komatsu Parts Support

- 24/7/365 to fulfill your parts needs
- 9 parts Distribution Centers strategically located across the U.S. and Canada
- Distributor network of more than 300 locations across U.S. and Canada to serve you
- Online part ordering through Komatsu eParts
- Remanufactured components with same-as-new warranties at a significant cost reduction



## Komatsu Oil and Wear Analysis (KOWA)

- KOWA detects fuel dilution, coolant leaks, and measures wear metals
- Proactively maintain your equipment
- Maximize availability and performance
- Can identify potential problems before they lead to major repairs
- Reduce life cycle cost by extending component life



# KOMTRAX EQUIPMENT MONITORING

GET THE WHOLE STORY WITH  
**KOMTRAX**<sup>®</sup>

✓ **WHAT**

- KOMTRAX is Komatsu's remote equipment monitoring and management system
- KOMTRAX **continuously monitors and records** machine health and operational data
- Information such as fuel consumption, utilization, and a detailed history **lowering owning and operating cost**

✓ **WHEN**

- Knowing when machines are **running or idling** can help improve fleet utilization
- Detailed movement records ensure you know when and where your equipment is moved
- Up to date records allow you to **know when maintenance is due** and help you plan for future maintenance needs

✓ **WHERE**

- KOMTRAX data **can be accessed virtually anywhere** through your computer, the web or your smart phone
- Automatic alerts keep fleet managers up to date on the latest machine notifications

✓ **WHY**

- Knowledge is power - **make informed decisions** to manage your fleet better
- Knowing your idle time and fuel consumption will help maximize your machine efficiency
- **Take control of your equipment** - any time, anywhere

✓ **WHO**

- KOMTRAX is **standard** equipment on all Komatsu construction products



**KOMTRAX**<sup>®</sup>

For construction and compact equipment.

**KOMTRAX Plus**<sup>®</sup>

For production and mining class machines.

# SPECIFICATIONS



## ENGINE

Model..... Komatsu SAA6D107E-3\*  
 Type ..... Water-cooled, 4-cycle, direct injection  
 Aspiration..... Komatsu Variable Geometry  
 Turbocharged, aftercooled, cooled EGR  
 Number of cylinders..... 6  
 Bore ..... 107 mm **4.21"**  
 Stroke ..... 124 mm **4.88"**  
 Piston displacement..... 6.69 ltr **408 in<sup>3</sup>**  
 Horsepower  
 ISO 9249 / SAE J1349 ..... Net 122.8 kW **165 HP**  
 Fan at maximum speed ..... Net 118.6 kW **159 HP**  
 Rated rpm ..... 2000 rpm  
 Fan drive method for cooling radiator ..... Mechanical with viscous fan clutch  
 Governor ..... All-speed control, electronic  
 \*EPA Tier 4 Final emissions certified



## HYDRAULICS

Type ..... HydraMind (Hydraulic Mechanical Intelligence New Design) system, closed-center system with load sensing valves and pressure compensated valves  
 Number of selectable working modes ..... 6  
 Main pump:  
 Type..... Variable displacement piston type  
 Pumps for..... Boom, arm, bucket, swing, and travel circuits  
 Maximum flow ..... 475 ltr/min **125.5 gal/min**  
 Supply for control circuit..... Self-reducing valve  
 Hydraulic motors:  
 Travel ..... 2 x axial piston motors with parking brake  
 Swing ..... 1 x axial piston motor with swing holding brake  
 Relief valve setting:  
 Implement circuits ..... 37.3 MPa 380 kg/cm<sup>2</sup> **5,400 psi**  
 Travel circuit..... 37.3 MPa 380 kg/cm<sup>2</sup> **5,400 psi**  
 Swing circuit..... 28.9 MPa 295 kg/cm<sup>2</sup> **4,190 psi**  
 Pilot circuit..... 3.2 MPa 33 kg/cm<sup>2</sup> **470 psi**  
 Hydraulic cylinders:  
 (Number of cylinders – bore x stroke x rod diameter)  
 Boom .. 2–130 mm x 1334 mm x 90 mm **5.1" x 52.5" x 3.5"**  
 Arm ..... 1–135 mm x 1490 mm x 95 mm **5.3" x 58.7" x 3.7"**  
 Bucket.. 1–115 mm x 1120 mm x 80 mm **4.5" x 44.1" x 3.2"**



## DRIVES AND BRAKES

Steering control..... Two levers with pedals  
 Drive method ..... Hydrostatic  
 Maximum drawbar pull ..... 202 kN 20570 kg **45,349 lb**  
 Gradeability..... 70%, 35°  
 Maximum travel speed: High ..... 5.5 km/h **3.4 mph**  
 (Auto-Shift) Mid ..... 4.1 km/h **2.5 mph**  
 (Auto-Shift) Low ..... 3.0 km/h **1.9 mph**  
 Service brake ..... Hydraulic lock  
 Parking brake ..... Mechanical disc brake



## SWING SYSTEM

Drive method ..... Hydrostatic  
 Swing reduction ..... Planetary gear  
 Swing circle lubrication ..... Grease-bathed  
 Service brake ..... Hydraulic lock  
 Holding brake/Swing lock..... Mechanical disc brake  
 Swing speed ..... 12.4 rpm  
 Swing torque..... 6900 kg•m **49,907 ft lbs**



## UNDERCARRIAGE

Center frame..... X-frame  
 Track frame..... Box-section  
 Seal of track ..... Sealed track  
 Track adjuster ..... Hydraulic  
 Number of shoes (each side) ..... 49  
 Number of carrier rollers (each side) ..... 2  
 Number of track rollers (each side) ..... 9



## COOLANT & LUBRICANT CAPACITY (REFILLING)

Fuel tank ..... 400 ltr **105.7 U.S. gal**  
 Coolant ..... 30.7 ltr **8.1 U.S. gal**  
 Engine..... 23.1 ltr **6.1 U.S. gal**  
 Final drive, each side..... 5.0 ltr **1.3 U.S. gal**  
 Swing drive ..... 6.5 ltr **1.7 U.S. gal**  
 Hydraulic tank ..... 132 ltr **34.9 U.S. gal**  
 Hydraulic system..... 234 ltr **61.8 U.S. gal**  
 DEF tank ..... 23.1 ltr **6.1 U.S. gal**



## OPERATING WEIGHT (APPROXIMATE)

Operating weight includes 5700 mm **18'8"** one-piece boom, 2925 mm **9'7"** arm, SAE heaped 1.19 m<sup>3</sup> **1.57 yd<sup>3</sup>** bucket, rated capacity of lubricants, coolant, full fuel tank, operator, and standard equipment.

Triple-Grouser Shoes	Operating Weight	Ground Pressure
700 mm	24160 kg	0.47 kg/cm <sup>2</sup>
<b>28"</b>	<b>53,265 lb</b>	<b>6.7 psi</b>
800 mm	24440 kg	0.42 kg/cm <sup>2</sup>
<b>31.5"</b>	<b>53,882 lb</b>	<b>5.9 psi</b>

### Component Weights

**Arm including bucket cylinder and linkage**  
 2900 mm **9'7"** HD arm assembly ..... 1136 kg **2,505 lb**  
 2900 mm **9'7"** HD arm assembly w/piping..... 1200 kg **2,646 lb**  
**One piece boom including arm cylinder**  
 5700 mm **18'8"** boom assembly..... 1885 kg **4,156 lb**  
 5700 mm **18'8"** HD boom assembly w/piping.. 1953 kg **4,306 lb**  
 Boom cylinders x 2 ..... 205 kg **452 lb**  
 Counterweight (standard) ..... 4370 kg **9,634 lb**  
 1.19 m<sup>3</sup> **1.57 yd<sup>3</sup>** bucket - 48" width ..... 949 kg **2,092 lb**






## DIMENSIONS

	Arm Length	2925 mm	9'7"
A	Overall length	9705 mm	31'10"
B	Length on ground (transport)	5000 mm	16'5"
C	Overall height (to top of boom)*	2995 mm	9'10"
D	Overall width	3080 mm	10'1"
E	Overall height (to top of cab)*	3045 mm	10'0"
F	Overall height (to top of handrail)*	3135 mm	10'3"
G	Ground clearance, counterweight	1085 mm	3'7"
H	Ground clearance, minimum	440 mm	1'5"
I	Tail swing radius	3020 mm	9'11"
J	Track length on ground	3655 mm	12'0"
K	Track length	4450 mm	14'7"
L	Track gauge	2380 mm	7'10"
M	Width of crawler	3080 mm	10'1"
N	Shoe width	700 mm	28"
O	Grouser height	26 mm	1"
P	Machine cab height	2250 mm	7'5"
Q	Machine height to top of engine cover	2765 mm	9'1"
R	Machine upper width	2850 mm	9'4"
S	Distance, swing center to rear end	2990 mm	9'10"

\* : Including grouser height



## BACKHOE BUCKET, ARM AND BOOM COMBINATION

Bucket Type	Bucket			5.7 m (18'8") Boom	
	Capacity	Width	Weight	2.9 m (9'7")	
Komatsu TL	0.50 m <sup>3</sup>	0.66 yd <sup>3</sup>	610 mm 24"	605 kg 1,334 lb	●
	0.67 m <sup>3</sup>	0.88 yd <sup>3</sup>	762 mm 30"	689 kg 1,518 lb	●
	0.85 m <sup>3</sup>	1.11 yd <sup>3</sup>	914 mm 36"	780 kg 1,719 lb	●
	1.02 m <sup>3</sup>	1.34 yd <sup>3</sup>	1067 mm 42"	857 kg 1,890 lb	○
	1.20 m <sup>3</sup>	1.57 yd <sup>3</sup>	1219 mm 48"	949 kg 2,092 lb	□
Komatsu HP	0.50 m <sup>3</sup>	0.66 yd <sup>3</sup>	610 mm 24"	652 kg 1,437 lb	●
	0.67 m <sup>3</sup>	0.88 yd <sup>3</sup>	762 mm 30"	763 kg 1,681 lb	●
	0.85 m <sup>3</sup>	1.11 yd <sup>3</sup>	914 mm 36"	868 kg 1,913 lb	●
	1.02 m <sup>3</sup>	1.34 yd <sup>3</sup>	1067 mm 42"	950 kg 2,095 lb	○
	1.20 m <sup>3</sup>	1.57 yd <sup>3</sup>	1219 mm 48"	1066 kg 2,349 lb	⊙
Komatsu HPS	0.50 m <sup>3</sup>	0.66 yd <sup>3</sup>	610 mm 24"	724 kg 1,597 lb	●
	0.67 m <sup>3</sup>	0.88 yd <sup>3</sup>	762 mm 30"	840 kg 1,851 lb	●
	0.85 m <sup>3</sup>	1.11 yd <sup>3</sup>	914 mm 36"	962 kg 2,120 lb	●
	1.02 m <sup>3</sup>	1.34 yd <sup>3</sup>	1067 mm 42"	1061 kg 2,339 lb	□
	1.20 m <sup>3</sup>	1.57 yd <sup>3</sup>	1219 mm 48"	1193 kg 2,630 lb	⊙
Komatsu HPX	0.50 m <sup>3</sup>	0.66 yd <sup>3</sup>	610 mm 24"	824 kg 1,817 lb	●
	0.67 m <sup>3</sup>	0.88 yd <sup>3</sup>	762 mm 30"	939 kg 2,071 lb	●
	0.85 m <sup>3</sup>	1.11 yd <sup>3</sup>	914 mm 36"	1061 kg 2,340 lb	○
	1.02 m <sup>3</sup>	1.34 yd <sup>3</sup>	1067 mm 42"	1161 kg 2,559 lb	□
	1.20 m <sup>3</sup>	1.57 yd <sup>3</sup>	1219 mm 48"	1293 kg 2,850 lb	⊙


● - Used with material weights up to 3,500 lb/yd<sup>3</sup> - Quarry/rock/high abrasion applications  
 □ - Used with material weights up to 2,500 lb/yd<sup>3</sup> - General construction

○ - Used with material weights up to 3,000 lb/yd<sup>3</sup> - Tough digging applications  
 ⊙ - Used with material weights up to 2,000 lb/yd<sup>3</sup> - Light materials applications  
 X - Not useable

# SPECIFICATIONS



## WORKING RANGE



	Arm Length	2925 mm	9'7"
A	Max. digging height	10000 mm	32'10"
B	Max. dumping height	7110 mm	23'4"
C	Max. digging depth	6620 mm	21'9"
D	Max. vertical wall digging depth	5980 mm	19'7"
E	Max. digging depth for 8' level bottom	6370 mm	20'11"
F	Max. digging reach	9875 mm	32'5"
G	Max. digging reach at ground level	9700 mm	31'10"
H	Min. swing radius	3040 mm	10' 0"

SAE rating	Bucket digging force at power max.	132 kN 13500 kg / <b>29,762 lb</b>
	Arm crowd force at power max.	103 kN 10500 kg / <b>23,149 lb</b>

ISO rating	Bucket digging force at power max.	149 kN 15200 kg / <b>33,510 lb</b>
	Arm crowd force at power max.	108 kN 11000 kg / <b>24,251 lb</b>


PC210LC-11



# LIFT CAPACITIES



## LIFTING CAPACITY WITH LIFTING MODE



- A: Reach from swing center
- B: Bucket hook height
- C: Lifting capacity
- Cf: Rating over front
- Cs: Rating over side
- ⊗: Rating at maximum reach


- Conditions:
- 5700 mm 18' 8" one-piece boom
  - Counterweight: 4370 kg 9,634 lb
  - Bucket: None
  - Lifting mode: On

Arm: 2900 mm 9'7" HD		Bucket: None				Shoes: 700 mm 28"				Unit: kg lb			
B	A	1.5 m 5'		3.0 m 10'		4.6 m 15'		6.1 m 20'		7.6 m 25'		⊗ MAX	
	MAX	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs
7.6 m 25'	6.0 m 20'											* 4100	* 4100
												* 9100	* 9100
6.1 m 20'	7.2 m 24'							* 6550	6100			* 3850	* 3850
								* 14400	13500			* 8500	* 8500
4.6 m 15'	7.9 m 26'					* 8000	* 8000	* 7200	5950	* 5250	4300	* 3800	* 3800
						* 17700	* 17700	* 15850	13200	* 11600	9500	* 8450	* 8450
3.0 m 10'	8.3 m 27'	* 12850	* 12850	* 10350	8650	* 8250	5750	6200	4200	* 3950	3700	* 3950	3700
		* 28300	* 28300	* 22850	19100	* 18200	12700	13650	9300	* 8700	8250	* 8700	8250
1.5 m 5'	8.4 m 27'			* 12550	8150	8400	5550	6050	4100	* 4200	3600	* 4200	3600
				* 27700	18050	18500	12200	13400	9050	* 9350	8000	* 9350	8000
0 m 0'	8.1 m 27'	* 7450	* 7450	12850	7900	8200	5350	6000	4000	* 4750	3700	* 4750	3700
		* 16500	* 16500	28300	17450	18100	11850	13200	8900	* 10500	8150	* 10500	8150
-1.5 m -5'	7.6 m 25'	* 12000	* 12000	12750	7800	8150	5300	* 5850	4000	* 5650	4000	* 5650	4000
		* 26500	* 26500	28100	17300	17950	11700	* 12950	8850	* 12550	8800	* 12550	8800
-3.0 m -10'	6.7 m 22'	* 18500	14950	12800	7900	8150	5350					7100	4700
		* 40850	33000	28250	17400	18050	11800					15650	10400
-4.6 m -15'	5.3 m 17'	* 14950	* 14950	* 10650	8100							* 8900	6650
		* 32950	* 32950	* 23500	17850							* 19700	14700

\*Load is limited by hydraulic capacity rather than tipping. Ratings are based on ISO standard No. 10567. Rated loads do not exceed 87% of hydraulic lift capacity or 75% of tipping load.



## LIFTING CAPACITY WITH LIFTING MODE



- A: Reach from swing center
- B: Bucket hook height
- C: Lifting capacity
- Cf: Rating over front
- Cs: Rating over side
- ⊗: Rating at maximum reach

- Conditions:
- 5700 mm 18' 8" one-piece boom
  - Counterweight: 4370 kg 9,634 lb
  - Bucket: None
  - Lifting mode: On

Arm: 2900 mm 9'7" HD		Bucket: None				Shoes: 800 mm 31.5"				Unit: kg lb			
B	A	1.5 m 5'		3.0 m 10'		4.6 m 15'		6.1 m 20'		7.6 m 25'		⊗ MAX	
	MAX	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs
7.6 m 25'	6.0 m 20'											* 4100	* 4100
												* 9100	* 9100
6.1 m 20'	7.2 m 24'							* 6550	6150			* 3850	* 3850
								* 14400	13650			* 8500	* 8500
4.6 m 15'	7.9 m 26'					* 8000	* 8000	* 7200	6050	* 5250	4350	* 3800	* 3800
						* 17700	* 17700	* 15850	13300	* 11600	9600	* 8450	* 8450
3.0 m 10'	8.3 m 27'	* 12850	* 12850	* 10350	8750	* 8250	5800	6250	4250	* 3950	3750	* 3950	3750
		* 28300	* 28300	* 22850	19250	* 18200	12850	13800	9400	* 8700	8300	* 8700	8300
1.5 m 5'	8.4 m 27'			* 12550	8250	8500	5600	6150	4160	* 4200	3650	* 4200	3650
				* 27700	18250	18700	12350	13550	9150	* 9350	8050	* 9350	8050
0 m 0'	8.1 m 27'	* 7450	* 7450	12950	8000	8300	5450	6050	4050	* 4750	3700	* 4750	3700
		* 16500	* 16500	28600	17650	18300	12000	13350	9000	* 10500	8250	* 10500	8250
-1.5 m -5'	7.6 m 25'	* 12000	* 12000	12850	7900	8200	5350	* 5850	4050	* 5650	4050	* 5650	4050
		* 26500	* 26500	28400	17450	18150	11850	* 12950	8950	* 12550	8900	* 12550	8900
-3.0 m -10'	6.7 m 22'	* 18500	15100	12950	7950	8250	5400					7150	4750
		* 40850	33350	28550	17600	18250	11900					15850	10500
-4.6 m -15'	5.3 m 17'	* 14950	* 14950	* 10650	8150							* 8900	6700
		* 32950	* 32950	* 23500	18050							* 19700	14850

\*Load is limited by hydraulic capacity rather than tipping. Ratings are based on ISO standard No. 10567. Rated loads do not exceed 87% of hydraulic lift capacity or 75% of tipping load.



### STANDARD EQUIPMENT

- 3 Speed travel with Auto shift
- Alternator, 90 Ampere, 24V
- AM/FM radio
- Automatic engine warm-up system
- Automatic air conditioner/heater
- Auto idle
- Auto Idle Shutdown (programmable)
- Lever lock Auto-lock
- Auxiliary input (3.5 mm jack)
- Batteries, large capacity
- Battery disconnect switch
- Boom and arm holding valves
- Carrier rollers (2 each side)
- Converter, (2) x 12V
- Counterweight, 4370 kg **9,634 lb**
- Dry type air cleaner, double element
- Electric horn
- EMMS monitoring system
- Engine, Komatsu SAA6D107E-3
- Extended work equipment grease interval
- Fan guard structure
- Fuel system pre-cleaner 10 micron
- High back air suspension seat, with heat
- Hydraulic track adjusters
- KOMTRAX® Level 5.0
- Large LCD color monitor, high resolution
- Lock lever
- Mirrors, (LH and RH)
- Operator Protective Top Guard (OPG), Level 1
- Operator Identification System
- Pattern change valve (ISO to BH control)
- Power maximizing system
- PPC hydraulic control system
- Pump/engine room partition cover
- Radiator and oil cooler dustproof net
- Rear reflectors
- Rearview monitoring system (1 camera)
- Revolving frame deck guard
- Revolving frame undercovers
- ROPS cab
- Seat belt, retractable, 76 mm **3"**
- Seat belt indicator
- Secondary engine shutoff switch
- Service valve
- Shoes, triple grouser, 800 mm **31.5"**
- Skylight
- Slip resistant foot plates
- Starter motor, 5.5kW/24V x 1
- Suction fan
- Thermal and fan guards
- Track frame undercover
- Track frame swivel guard
- Travel alarm
- Working lights, 2 (boom and RH front)
- Working mode selection system



### OPTIONAL EQUIPMENT

- (1) additional rearview camera
- Arms
  - 2925 mm **9'7"** HD arm assembly
  - 2925 mm **9'7"** HD arm assembly with piping
- Booms
  - 5700 mm **18'8"** boom assembly
  - 5700 mm **18'8"** HD boom assembly with piping
- Cab guards
  - Full front guard, OPG Level 1
  - Full front guard, OPG Level 2
  - Bolt-on top guard, OPG Level 2
  - Lower front window guard
- High pressure in-line hydraulic filters
- Hydraulic control unit, 1 actuator
- Rain visor
- Revolving frame undercovers, heavy duty
- Shoes, triple grouser, 700 mm **28"**
- Sun visor
- Straight travel pedal
- Track roller guards, full length
- Working light, front, one additional



### ATTACHMENT OPTIONS

- Cab air pre-cleaner
- Grade control systems
- Hydraulic couplers
- Hydraulic kits, field installed
- Super long fronts
- PSM thumbs
- Rockland thumbs
- Vandalism protection guards with storage box

**For a complete list of available attachments, please contact your local Komatsu distributor.**



*Note: All comparisons and claims of improved performance made herein are made with respect to the prior Komatsu model unless otherwise specifically stated.*