45 ton *(40.8 mt)* Telescopic Crawler Crane

- Remarkable control, reliability &

450

100

Ε

S

Ν

R

С

Α

Link-Bett

- Remarkable control, reliability & capacity performance
 Unprecedented attachment flexibility
 Wireless rated capacity limiter
 Unbeatable hydraulic pilot-operated control
 Fits in places no other rough terrain nor crawler can
 Quick mobilization transports in one load
- transports in one load





45-ton (40.8 mt) Telescopic Crawler Crane

Remarkable control, reliability and capacity performance

- Whisper quiet Isuzu engine with 197 hp (146.90 kW)
- Main drum grooved for 18mm wire rope with 17,916 lbs (8 127 kg) available line pull
- Mechanical drum rotation indicators
- 340 fpm (103.7 m/min) line speed
- Optional auxiliary hoist winch
- Optional auxiliary lifting sheave off main boom



4-section full power boom with attachment flexibility

- Full power 33 ft to 105 ft (10.06 m to 32.0 m) four-section boom
- Exclusive A-max mode offers substantially increased capacities in close. Standard "B" mode extends all four sections equally.
- **Maximum boom/jib length** is 105 ft + 20 ft (*32 m* + 6.09 *m*)
- Lightweight nylon head sheaves reduce overall machine weight and increase lift capacities
- Quick reeve boom head allows rope to be easily reeved over boom head
- Hammerhead boom nose allows operator to work at high boom angles
- Optional 20 ft (6.09 m) one-piece swing-away fly



Ergonomically designed for maximum visibility, comfort and control

- Wireless rated capacity limiter
- Sliding left side door, right and rear windows, and swing up top window provide excellent ventilation
 AM/FM radio
- Air conditioner / hot water heater
- Hand and foot throttle
- Travel pedals
- Single axis controls



32" grouser track shoes form a wide gauge of 11' 2" (3.40 m) when extended, and 8' 9" (2.66 m) when retracted with two position house lock.

Quick mobilization & superb job-site mobility

- Transports COMPLETE ONE LOAD
- Fold-up catwalks
- Hydraulic retractable side frames for transport





Link-Belt Construction Equipment Company Lexington, Kentucky www.linkbelt.com

® Link-Belt is a registered trademark. Copyright 2007. All rights reserved. We reserve the right to change designs and specifications at any time. Litho in U.S.A. 10/07 536 #4340 (supersedes #4329)