

MODEL 644B-37

SPECIFICATIONS

ENGINES:

- JOHN DEERE — 4039D
80 HP @ 2500 RPM
- JOHN DEERE — 4045T
100 & 115 HP @ 2500 RPM
- CUMMINS — 4B3.9
76 HP @ 2500 RPM
- CUMMINS — 4BT3.9
110 HP @ 2500 RPM

TRANSMISSION:

- 3-SPEED POWER SHIFT, FWD. & REV.
- COLUMN-MOUNTED SHIFT LEVER
- NEUTRAL START SWITCH
- H.D. TRANSMISSION OIL COOLER
- DECLUTCH SWITCH ALLOWS BRAKE PEDAL TO DISENGAGE TRANSMISSION WHEN BRAKE IS APPLIED.

AXLES:

- OUTBOARD PLANETARY WITH DOUBLE REDUCTION
- 4-WHEEL DRIVE
- LIMITED SLIP FRONT DIFFERENTIAL
- STEERING — 3 MODES: 4 WHEEL ROUND, 2 WHEEL FRONT, AND 4 WHEEL CRAB
- HYDRAULIC FULL POWER STEERING WITH 2 DOUBLE-ACTING STEER CYLINDERS PER AXLE

BRAKES:

- 4-WHEEL, FULLY ENCLOSED, WET DISC
- HYDRAULIC ACCUMULATOR STORED ENERGY BRAKING FOR DEAD ENGINE STOPS
- "FAIL-SAFE" PARK BRAKE: SPRING APPLIED HYDRAULIC RELEASE
- DASH-MOUNTED INDICATOR LIGHTS

ELECTRICAL SYSTEM:

- 12 VOLT, NEGATIVE GROUND
- 925 AMP COLD CRANKING, MAINTENANCE FREE BATTERY
- 65 AMP H.D. ALTERNATOR
- CIRCUIT BREAKER PROTECTED SYSTEM

FILTRATION:


- AIR CLEANER — 2 STAGE DRY TYPE WITH REPLACEABLE ELEMENTS. (VISUAL SERVICE IND. STD.)
- ENGINE OIL LUBE — FULL FLOW SPIN-ON CARTRIDGE TYPE WITH BYPASS
- FUEL FILTER WITH WATER SEPARATOR & DRAIN.
- TRANSMISSION — SPIN-ON TYPE WITH SAFETY BYPASS
- MAIN HYDRAULICS — 10 MICRON FULL FLOW FILTER ELEMENT WITH SAFETY BYPASS

HYDRAULIC SYSTEM:

- 2-SECTION GEAR PUMP: 18 GPM TO MAIN HYDRAULICS, 18 GPM TO STEERING, BRAKE PRIORITIES AND HYDRAULIC SYSTEM. EXTRA FINE METERING & SELF CENTERING HYDRAULIC CONTROL VALVES.

STANDARD EQUIPMENT:

- SEAT BELT
- HORN
- REVERSE WARNING ALARM
- NEUTRAL START SWITCH
- SKID RESISTANT FLOOR MATERIAL
- RIGHT SIDE REAR VIEW MIRROR
- ANTI-FREEZE PROTECTION TO - 30°F
- MACHINE LEVEL INDICATOR



STANDARD EQUIPMENT (cont'd):

- FULL INSTRUMENTATION INCLUDING: FUEL GAUGE, WATER TEMP. GAUGE, HOUR METER, OIL PRESSURE GAUGE, TRANS. OIL TEMP. GAUGE, VOLT METER, PARK BRAKE APPLIED LIGHT, LOW BRAKE PRESSURE LIGHT, TRANS. DECLUTCH LIGHT
- AUTOMATIC FORK LEVELING
- HYD/HYD. JOYSTICK CONTROLS (PILOT OPERATED)
- 2-SECTION "FULL" HYDRAULIC SLIDE BOOM
- FIRST AUXILIARY HYDRAULICS TO BOOM TIP
- FRAME LEVELING 12-1/2° L & R
- TIE DOWN LUGS
- 13:00 X 24 - 10 PLY TIRES
- QUICK ATTACH
- REAR AXLE STABILIZER SYSTEM
- OPERATOR'S COMPARTMENT ROPS/FOPS
- CONFORMS WITH ANSI/ASME B56.6, 1992

OPTIONAL EQUIPMENT:

- 50.5" FORK CARRIAGE
- 50.5" SIDE TILTING CARRIAGE (10° R-L)
- DUAL FORK POSITIONING CARRIAGES AVAILABLE IN WIDTHS 50.5" OR 74"
- 74" STANDARD FRAMERS CARRIAGE
- 74" SIDE TILTING FRAMERS CARRIAGE (10° R-L)
- 2" X 4" - 42"/48"/60" FORKS
- 1-3/4" X 6" - 48"/60" LUMBER FORKS
- 2" X 2" CUBING FORKS - ORDER IN PAIRS
- AUXILIARY HYDRAULICS FOR SECOND ACCESSORY
- 1.25 CU YD BUCKET (LIGHT MATERIAL)
- 4,500 LB CAPACITY HYDRAULIC WINCH, BOOM MOUNTED
- CAB ENCLOSURE
- HEATER/DEFROSTER
- AIR CONDITIONING
- 10' TRUSS BOOM (W/WO 2,000 LB CAP. HYDRAULIC OPERATED WINCH)
- ROADWAY LIGHT PACKAGE
- WORK LIGHT PACKAGES
- 3/4 CU YD HYDRAULIC OPERATED CONCRETE HOPPER

OPERATING SPECIFICATIONS:

LIFT AND CARRY CAPACITY	6,000 LBS
MAX. LIFT HEIGHT	37'
MAX. "LANDING HEIGHT"	37'
TRANSACTION	80"
MAX. HORIZONTAL FORWARD REACH	27'
MAX. REACH @ MAX. LIFT	8'
CAPACITY @ MAX. REACH	1,000 LBS
BELOW GRADE	16"
OUTSIDE TURNING RADIUS	13' 8"
GROUND CLEARANCE	16"
OVERALL HEIGHT	95"
OVERALL WIDTH	8'
OVERALL LENGTH	25'9" (W/42" Forks)
WHEELBASE	124"
WEIGHT	20,860 LBS

CAPACITIES:

FUEL	40 GAL.
COOLING SYSTEM	18 QTS.
CRANK CASE W/ FILTER	14 QTS
HYDRAULIC RESERVOIR	44 GAL.
BATTERY	12 VOLT 925 CCA

Authorized Representative:



3045 Highway 13, St. Paul, MN 55121

Lull reserves the right to make improvements in design and changes in specifications without notice and without incurring obligation as to units already sold.

© Copyright 1994 Lull International, Inc. All Rights Reserved 12/95-10M