

MANITOU

K-D Hawk



- Lift Capacity: 6,000 lb.
- Lift Heights to 12 ft. 4 in.
- Two Cab Heights
- Special Poultry Features



Courtesy of Crane.Market

K-D HAWK



Lift Capacity

Maximum (24 in. load center)6,000 lb.
Maximum (48 in. load center)3,600 lb.



Lift Height:

Max. lift height148 in.



Tires:

Standard Drive (Front) 81"/100" ...17.5L24 x 12
Standard Drive (Front) 77"15 x 19.5
Standard Steer (Rear)12 x 16.5



Forks:

Length84 in.
Width5 in.
Thickness1.75 in.



Brakes:

Service ...Fully enclosed, oil-immersed disc type
Parking brakeMechanical



Engine Options:

ModelCaterpillar or Perkins
TypeDiesel
Displacement4 cyl. - 236 cu. in.
Power80 HP
Rated Speed2200 RPM



Transmission Options:

TypeHydrostatic or Torque Convertor
Max. travel speed16 mph



Hydraulics:

PumpGear type
Flow25 gpm



Capacities:

Cooling system5 gal.
Engine oil2.75 gal.
Fuel tank26 gal.
Hydraulic fluid26 gal.



Specifications:

Weight14,500 lb.
Turning radius (center of wheels)117 in.
Overall length (without forks)149 in.

Mast Selections & Capacities

(Based on 48 in. Load Center)

MFH

CAPACITY

	148"	
135"	3,600 lb.	3,600 lb.
OHL	77"	81"
MFH	135"	148"
FFH	16"	16"

3-Stage Low-Profile "Total Visibility" Roller Mast
with Optional Rotator Carriage

DIMENSIONS:...

100"81"77"

A.....8484.....84

B.....8585.....85

C373737

D150150.....150

E.....234234.....234

F.....70.570.5.....66.5

F₁.....71.571.5.....68.5

G1313.....12

G₂.....9.59.5.....9.5

I2828.....28

U10081.....77

W.....87.587.5.....82

Y10°10°10°

Z45°45°45°

(with rotator attachment)

STANDARD EQUIPMENT:

- 80 H.P. Four Cylinder Diesel Engine
- 2 Wheel Drive
- Heavy Duty Steer Axle
- Side Shift Mast
- Hydraulic Load Accumulator
- 4 Spool Hydraulic Valve Assembly
- Rubber Mounted Tilting Operator's Compartment
- Gauge Package
- Poultry Light Package
- Backup Alarm
- Tow Pin

OPTIONAL EQUIPMENT:

- Semi-Enclosed Cab
- Rotator Carriage
- 4 Wheel Drive

