



Industrial Grade Electric Scissor Lifts

Models
2047ES
2647ES
3247ES

- Fully proportional drive and lift controls
- No-maintenance scissor bearings
- Roll-out deck extension with incremental locking positions
- Non-skid, steel deck construction
- Large sheet loading entrance
- Single arm scissor provides easy access for maintenance. No need for swing-out stations or tight working conditions.
- Patented Powerlift² elevating system - built strong and works tough
- High torque power package
- Higher capacity (up to 1,250 lbs/ 566 kg) expands applications and productivity



Features

Work Area

Roll-out deck extension with incremental locking positions
 Large sheet loading entrance accommodates 48" (1.22 m) material
 110V Power to Platform
 Combination of wide beams and large pins in self-lubricating bearings for larger load bearing surface in scissor pivot areas
 Extra wide platform for spacious work area

Performance

Fully Proportional Drive and Lift Controls
 High Torque Power Package

Engine/Power

Four 6V 220Ah Industrial Deep Cycle Batteries (245Ah on 3247ES)

Serviceability

Lubrication-Free Scissor Bearings
 Specially designed hydraulic swivel fittings to reduce hydraulic hose binding and hose failure
 Easy maintenance access to mechanical and electrical components without raising platform or swinging out trays
 Logically grouped components and numbered wiring for easy reference

Safety

Dedicated compartments protect electrical and hydraulic components
 Emergency shut-off at platform and lower controls
 Non-Skid Steel Deck Construction
 Motion Alarm
 Drive Speed Interlock
 Multi-Axis Tilt Sensor
 Multiple Disc Brakes, manual brake release
 Scissor Maintenance Lock
 Dual Automatic Parking Brake
 Automatic Pothole Protection

Other Features

Industrial grade, solid state battery charger
 Fold-Down Guardrails
 Non-Marking Tires
 Hour Meter
 Powder Coat Finish
 Lifting Lugs
 Machine Tie Downs
 Fork Lift Pockets
 Static Strap
 U.S. Patent #5,476,050
 Canadian Patent #2,115,870
 Other Patents Pending

Optional Features

Lanyard Attachments (6)	Audible Motion Alarm
Flashing Beacon (continuous)	Battery Charge Indicator
Automotive Horn	245Ah Deep Cycle Batteries
Removable Upper Controls	800 Watt AC Inverter
Platform Swing Gate (standard on CE and CSA)	Australian Compliant Options
Air Line to Platform	CSA Compliant Options
	1 or 2 Year Extended Warranty



MEC Aerial Work Platforms

1775 Park Street, #77 | Selma, CA 93662 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438
 Tel: 559.891.2488 | Fax: 559.891.2448
 Email: info@mecAWP.com
 www.mecAWP.com

Model	2047ES		2647ES		3247ES	
	U.S.	Metric	U.S.	Metric	U.S.	Metric
Heights						
Working Height*	26 ft.*	8.10 m*	32 ft.*	9.92 m*	38 ft.*	11.75m*
Platform Height	20 ft.	6.10 m	26 ft.	7.92 m	32 ft.	9.75 m
Maximum Drive Height	20 ft.	6.10 m	26 ft.	7.92 m	32 ft.	9.75 m
Stowed Height (Top Guardrail)	82 3/8 in.	2.10 m	88 3/8 in.	2.25 m	95 1/8 in.	2.42 m
Stowed Height (Rails Folded)	63 3/4 in.	1.62 m	70 in.	1.78 m	76 3/16 in.	1.94 m
Stowed Height (Platform Floor)	40 1/2 in.	1.03 m	47 in.	1.19 m	53 in.	1.35 m
Guardrail Height	43 3/8 in.	1.10 m	43 3/8 in.	1.10 m	43 3/8 in.	1.10 m
Toeboard Height	6 in.	15 cm	6 in.	15 cm	6 in.	15 cm
Ground Clearance	3 1/2 in.	8.89 cm	3 1/2 in.	8.89 cm	3 1/2 in.	8.89 cm
Pothole Guards Deployed	3/4 in.	1.90 cm	3/4 in.	1.90 cm	3/4 in.	1.90 cm
Dimensions						
Length - Stowed (Overall)	99 in.	2.51 m	99 in.	2.51 m	99 in.	2.51 m
Length - Stowed (Without Step)	92 1/2 in.	2.35 m	92 1/2 in.	2.35 m	92 1/2 in.	2.35 m
Width	47 in.	1.19 m	47 in.	1.19 m	47 in.	1.19 m
Platform Length (Extended)	133 1/2 in.	3.39 m	133 1/2 in.	3.39 m	133 1/2 in.	3.39 m
Platform Length (Retracted)	91 in.	2.31 m	91 in.	2.31 m	91 in.	2.31 m
Roll-Out Deck Length	42 1/4 in.	1.07 m	42 1/4 in.	1.07 m	42 1/4 in.	1.07 m
Wheelbase	71 in.	1.80 m	71 in.	1.80 m	71 in.	1.80 m
Lift Capacity	1,250 lbs	567 kg	1,000 lbs	454 kg	700 lbs	318 kg
Roll-Out Deck Capacity	250 lbs	113 kg	250 lbs	113 kg	250 lbs	113 kg
Speeds						
Raise/Lower Speed	28/35 sec.		30/35 sec.		42/32 sec.	
Drive Speed (Stowed)	2.5 mph	4.0 km/h	2.5 mph	4.0 km/h	2.5 mph	4.0 km/h
Drive Speed (Raised)	0.62 mph	1.0 km/h	0.62 mph	1.0 km/h	0.62 mph	1.0 m/h
Performance						
Gradeability	25%/14°		25%/14°		25%/14°	
Turning Radius (Inside)	Zero		Zero		Zero	
Turning Radius (Outside)	94 in.	2.39 m	94 in.	2.39 m	94 in.	2.39 m
Weight (Approximately**)	4,450 lbs**	2018 kg**	5,300 lbs**	2404 kg**	5,990 lbs**	2717 kg**
Brakes	Dual rear wheel multi-disc					
Power Source	24V DC, 220Ah battery (245Ah on 3247ES)					
Drive Axle	Dual front wheel hydraulic					
Controls	Proportional drive and lift controls					
Tires (Non-Marking)	16 in. D x 5 in. W/40.64 cm D x 12.70 cm W					

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may increase with certain options or configurations. When platform is elevated, all models must be on a firm, level surface.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.6-2006, CSA B354.2-01, AS 1418.10 and CE Compliance as applicable. Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: