



THE QUICKEST LOADER OUT THERE UNMATCHED AGILITY. UNPARALLELED PRECISION.

The ELITE is without question the toughest, most versatile, longest lasting knuckle boom loader of its size. With the industry's lowest total cost of ownership, the ELITE is quickly becoming the favorite of owners and operators around the globe. Available in a variety of configurations, we have a solution for every conceivable application. The ELITE and all of its major components are designed and manufactured by Rotobec right here in North America. If you are looking to lift more in less time than ever before, look no further, the ELITE is your only option.



ELITE 910

5,000 LBS TOTAL WEIGHT

8,800 LBS MAX LIFT CAPACITY

22 FT HEAVY DUTY BOOM (STANDARD)

20 GPM PUMP FLOW

3,000 PSI OPERATING PRESSURE

8 SEC MAIN BOOM CYCLE



10,960 LBS MAX LIFT CAPACITY

28 IN SLEWING RING

23 FT HEAVY DUTY BOOM (STANDARD)

3,200 PSI OPERATING PRESSURE

<mark>10 SEC</mark> MAIN BOOM CYCLE

ULTIMATE EFFICIENCY

INCREASE YOUR PAYLOAD

The ELITE 910 is without a doubt, the lightest loader available. Better fuel efficiency and more weight available for materials on your truck or trailer equates to more money in your pocket.

SPEED MACHINE

With a pump flow of 19 gpm and a lightning fast main boom cycle time of 8 seconds, the ELITE 910 will let you move more in less time than ever before. Spend less time repositioning your loader and more time on what matters most: Working.

LITTLE GIANT

The lightweight design of the ELITE 915, combined with an incredible 10,960 lbs of max lift capacity, make it the undisputed heavyweight champion in its weight class. Lift more with less than you ever imagined.

SMOOTH MOVEMENT

The 3,200 psi operating pressure allows the ELITE 915 to achieve unmatched levels of precision making it a dream to operate. Whether you're a rookie or a seasoned vet, this loader will make even the most inexperienced operator look like a pro.

ENDLESS POSSIBILITIES

We understand that no two jobs are alike. Every industry and every environment have their own unique requirements. That's why we offer an extensive list of exclusive options on the ELITE to suit all of your needs. If you're looking for something we haven't thought of, let us know. Rotobec is proud to offer complete customization on all of our products.

CUSTOMIZATION

Rotobec has been designing and manufacturing loaders for 40 years. During that time, our custom loader division has worked on several projects for customers who had unique requirements that the competition could simply not meet. Our team of engineers worked closely with these customers to provide them with a solution to meet those needs.

If you have a requirement that is not met by our current product let us know. Rotobec is open to any custom project and we are always looking for a new challenge.

OPTIONS

- Rotocab
- Wipers
- Roof lights
- 4,000 W heater
- Air conditioning
- AM/FM/CD Radio
- Heated joysticks
- Grapple saw hydraulic circuit
- Multiple boom lengths
- Double pump hydraulic system
- Custom colors
- 55 gal oil tank
- Boom guard









A LOADER FOR EVERY APPLICATION

The ELITE is used in every industry in a variety of applications. Its precision and agility make it the ideal machine for everything from log loading to railway maintenance and construction. No matter what the application, the ELITE loader is fit for the job.

FORESTRY Used for the loading and unloading of trucks. Can be mounted on both on and off road vehicles.

WASTE Used commonly by municipalities for roadside waste collection and disaster clean up.

RAIL Used in rail applications for the delivery to and clean up of components at railway maintenance sites.

SCRAP & RECYCLING Used for the collection and transportation of scrap and recycling materials to processing facilities.

NO TIME FOR DOWNTIME

The ELITE and nearly all of its components are designed and manufactured at our North American production facilities. We are dedicated to providing you with the most durable and reliable loaders on the market. Because we manufacture everything in house, our parts availability is second to none and our service team is committed to ensuring that your loader is running at maximum capacity at all times.

QUALITY COMPONENTS

Each component of the ELITE is manufactured in house using the highest quality materials. Our components are built with one purpose: To outperform and outlast the competition.

SERVICE MADE SIMPLE

Rotobec engineers have designed the ELITE in a way that makes it incredibly simple to service. With no need for special tools, the ELITE can even be serviced in the field maximizing your machine uptime.

Telescopic

KEY SPECIFICATION - ELITE 915

KEY SPECIFICATION - ELITE 910					
Structure	Rectangular 6" x 8" structure made of high tensile steel				
Pivots	2" diameter heat-treated and chromed pins mount on bronze bushings				
Stabilizers	3" bore, 2" rod				
Complete motion	Main: 9 sec w/ 19 gpm Stick: 7 sec w/ 19 gpm				
Slewing ring	27" outside diameter				
Rotation speed	9 rpm				
Weight	4,940 lbs (with standard boom)				
Operating pressure	3,000 psi				
Swing torque	Theoretical: 15,987 ft. lb @ 3,200 psi Actual: Estimated at 13,589 ft. lb				

BOOM LENGTH OPTIONS - ELITE 910 22' Standard Non-telescopic 21', 25' (other lengths available upon request)

Structure	Rectangular 7"x 8" structure made of high tensile steel		
Pivots	2.5" diameter heat-treated and chromed pins mounted on bronze bushings		
Stabilizers	3.5" bore, 2" rod		
Complete motion	Main: 9 sec w/ 22 gpm Stick: 8 sec w/ 22 gpm		
Slewing ring	28" outside diameter		
Rotation speed	8 rpm		
Weight	6,163 lbs (with standard boom)		
Operating pressure	3,200 psi		

26', 27' (other lengths available upon request)

BOOM LENGTH OPTIONS - ELITE 915

Standard	23'
Telescopic	26', 28'

ELITE 910 - LIFT CAPACITY (lb)

		DISTANCE FROM CENTER OF ROTATION (ft)				
	HEIGHT (ft)	5	10	15	20	
Ď.	30		6,520			
M-25	25			5,200		
ELITE 910 T&T - M-2 <i>2</i> °	20			5,290	3,920*	
910	15	7,660*	7,690	5,670	4,390	
Ë	10	3,580*	8,770	5,890	4,150	
	5	5,380*	8,160	5,350	3,070	
	0		5,500	3,390		



FEATURES & OPTIONS

SWING SYSTEM - ELITE 910/915

- Continuous 360° rotation
- Pedal activated rotation
- Locking mechanism for transportation mode

CYLINDERS - ELITE 910/915

Features

- Bolt-on head
- Wear ring
- Chrome plated tempered steel rod

BOOM - ELITE 910/915

Features

- Induction tempered, chrome steel pins on bronze bushings
- Telescopic booms activated by electric button and proportionately controlled by lever
- Designed for closer access to loader frame
- 2 x 55 W halogen work lights
- Main/Stick boom: 5" bore, 3" rod

HYDRAULIC SYSTEM - ELITE 910/915

Features

- Double function joystick
- 2 x 19 gpm @ 1,800 rpm pump flow (910)
- 2 x 22 gpm @ 2,100 rpm pump flow (915)
- 8 port hydraulic oil manifold

ELITE 915 - LIFT CAPACITY (lb)

		DISTANCE FROM CENTER OF ROTATION (ft)			
	HEIGHT (ft)	5	10	15	20
ço	30			4,500*	
M-2	25			5,490	
ELITE 915 T&T - M-23'	20		6,680	5,760	5,090
88	15	10,960***	8,660	6,430	5,220
	10	2,160*	10,390	7,000	5,240
	5	5,060*	10,300	6,860	4,650
	0	8,720*	8,160	5,380	

- * Limited by stick boom hydraulic capacity
- ** Lift capacities calculated at 100% operating pressure
- *** Maximum load that must never be exceeded = 10,960 lbs
- **** We reserve the right to change specification and improve our products without notice or obligation

CANADA EAST/ INTERNATIONAL Sainte Justine, QC Tel: 418.383.3002

USA EAST, CENTRAL USA SOUTH Littleton, NH Tel: 603.444.2103

Dallas, TX Tel: 972.242.9516 USA/CANADA **WEST** Kelowna, BC Tel: 250.765.1161 **BRAZIL** Curitiba, Paraná Tel: 41.98852.5999

