

SPH STEPP PREMIX HEATERS



12325 River Road / North Branch MN 55056 ~ P: 651-674-4491 F: 651-674-4221 ~ jason@steppmfg.com ~ branda@steppmfg.com

The Stepp Trailer Mounted Pre-mix Heater "asphalt hot box" is the perfect blend of performance, durability and versatility for your pothole patching needs and budget. Whether your application is to keep your Hot Mix at temperature or reclaiming asphalt the SPH Line will meet your needs.

Available Sizes...

- SPH 1.5 Cubic Yards (2 Ton Capacity)
- SPH 2.0 Cubic Yards (3 Ton Capacity)
- SPH 3.0 Cubic Yards (4 Ton Capacity)

Design Benefits...

- Heavy duty construction
- Modular design for specific customization
- Digital Electronic Thermostats for precise temperature control, safety and easy operation
- Heat Riser in the center of the hopper puts the heat where its needed most.
- Sloped design of the hopper allows material to "flow" to the shovel platform for easy dispensing.
- Top Door Lift Assist is equipped with gas operated shocks to assist in top door opening
- Stainless Steel Shovel Platform



Options...

- Heated or Unheated Tack Tank
- Heated 15' and 20' Hose
- Material Pumping System
- Shovel Cleaning Compartment
- Tool Holders
- Tool Box
- Arrow Board



VISIT US ONLINE AT:

www.steppmfg.com OR <https://www.facebook.com/steppmfg>

Courtesy of Machine.Market

Quick Spec	SPH 1.5	SPH 2.0	SPH 3.0
Capacity	1.5 Cubic Yard 2 Ton	2.0 Cubic Yard 3 Ton	3.0 Cubic Yard 4 Ton
Empty Weight	3,000 lbs.	3,500 lbs.	3,900 lbs.
GVWR	7,000 lbs.	12,000 lbs.	14,000 lbs.
Dimensions (LxWxH)	208"x 90"x 68"	208"x 90"x 76"	208"x 90"x 90"
Diesel Burner BTU	120,000 BTU	120,000 BTU	120,000 BTU
LP Burner BTU	250,000 BTU	250,000 BTU	250,000 BTU
Frame Construction	2"x 6"x 3/16" Rectangular Steel Tubing	2"x 6"x 3/16" Rectangular Steel Tubing	2"x 6"x 3/16" Rectangular Steel Tubing
Axle	Single 7,000 lbs.	Tandem 6,000 lbs.	Tandem 7,000 lbs.
Tires	235/80R16	225/75R15	235/80R16
Brakes	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)	Electric (std) Hydraulic (opt)
Hitch	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball	3" Pintle or 2-5/16" Ball
Hitch Height	Adjustable 24"-32"	Adjustable 24"-32"	Adjustable 24"-32"