

TMD DIGGER DERRICK

TMD-2042T/TMD-2045T/TMD-2047T/TMD-2050T



The **VERSALIFT** product line has grown to encompass models for every market. Whether it be a 29' man lift or a 108' material handler, there is a **VERSALIFT** to get the job done.

For more information

Versalift
254.399.2100
www.VERSALIFT.com

TMD T SERIES

Utilities Material Handler



General Specifications	TMD-2042T	TMD-2045T	TMD-2047T	TMD-2050T
Maximum Capacity	28900 lb. (13110 kg.)	27500 lb. (12470 kg.)	25000 lb. (11340 kg.)	25000 lb. (11340 kg.)
Capacity at 10ft Radius	12700 lb. (5760 kg.)	12400 lb. (5620 kg.)	11800 lb. (5350 kg.)	11800 lb. (5350 kg.)
HORIZONTAL REACH				
Horizontal Reach (B1)	16.8 ft. (5.1 m.)	17.8 ft. (5.4 m.)	19.8 ft. (6.0 m)	19.8 ft. (6.0 m)
Horizontal Reach (B2)	24.8 ft. (7.6 m.)	26.8 ft. (8.2 m.)	28.8 ft. (8.8 m)	30.3 ft. (9.2 m)
Horizontal Reach (B3)	32.8 ft. (10.0 m.)	35.8 ft. (10.9 m.)	37.8 ft. (11.5 m)	40.8 ft. (12.4 m)
SHEAVE HEIGHT				
Sheave Height (A1)	27.4 ft. (8.4 m)	28.4 ft. (8.7 m)	30.4 ft. (9.3 m)	30.4 ft. (9.3 m)
Sheave Height (A2)	35.3 ft. (10.8 m)	37.3 ft. (11.4 m)	39.3 ft. (12.0 m)	40.7 ft. (12.4 m)
Sheave Height (A3)	43.2 ft. (13.2 m)	46.1 ft. (14.1 m)	48.1 ft. (14.7 m)	51.1 ft. (15.6 m)
LOAD RADIUS				
Load Radius (R1)	3.6 ft. (1.1 m)	3.7 ft. (1.1 m)	4.1 ft. (1.2 m)	4.1 ft. (1.2 m)
Load Radius (R2)	5.0 ft. (1.5 m)	5.3 ft. (1.6 m)	5.6 ft. (1.7 m)	5.9 ft. (1.8 m)
Load Radius (R3)	6.3 ft. (1.9 m)	6.9 ft. (2.1 m)	7.2 ft. (2.2 m)	7.7 ft. (2.3 m)
DIG RADIUS				
Dig Radius (S1)	14.3 ft. (4.4 m)	15.3 ft. (8.7 m)	17.3 ft. (5.3 m)	17.3 ft. (5.3 m)
Dig Radius (S2)	22.3 ft. (6.8 m)	24.3 ft. (7.4 m)	26.3 ft. (8.0 m)	27.8 ft. (8.5 m)

OPTIONS:

- Fiberglass Platform
- Liners Available
- Hard-Wired Electric/Hydraulic Lower Controls
- Radio Remote Controls
- Full Pressure Upper Controls with Boom Sequencing
- Various Single Stick Handles
 - Standard VERSALIFT Handle
 - T-Handle
- 5 FT Underslung Jib

- Hydraulic Tool Power Outlets
- Multi-Part Line Components
- Various Types of Outriggers
- Various Augers
- Various Digger Drives
- Left-Hand Riding Seat
- Lower Boom Stow Limit
- Riding Seat Access Ladder

NOTE:

1. Specifications may vary without prior notice
2. Required GVWR can vary significantly with chassis, lift mounting, location, service body, accessories and desired payload.

