



VST-9000-MHI

Articulated Telescopic Aerial Device

DEMAND BETTER.



- Max jib capacity: 1000 lbs



- Bucket capacity: 700 lbs
(with jib installed)/800 lbs
(without jib installed)



- Working height: 94'11"
- Horizontal reach: 56'8"



For more information about any of our outstanding VERSALIFT products, contact your authorized VERSALIFT Distributor or call 1.800.825.1085.



VST-9000-MHI

Articulated Telescopic Aerial Device

GENERAL SPECIFICATIONS

VST-9000-MHI

Horizontal Reach Overcenter	56'8"
Maximum Bucket Capacity	700 lbs. (with jib installed)/800 lbs. (without jib installed)
Lower Boom Lift Eye Capacity	1,500 lbs. (680kg)
Maximum Jib Capacity	1,000 lbs. (454kg)

HEIGHT WITH STANDARD REVERSE MOUNT PEDESTAL

Height to Bottom of Platform	89'11"
Working Height	94'11"
Stowed Travel Height	12'5"

HYDRAULIC SYSTEM

Operating Pressure	3000 psi (205 bars)
Flow Rate	10 gpm (38 lpm)
Filtration	10 Micron Return; 100 mesh Suction
System Type	Open Center
Power Source	PTO Pump

BOOM ACTION

Upper Boom Articulation	-25° to +75°
Lower Boom Articulation	0° to +88°
Inner boom extension	198"
Rotation	360° Continuous
Platform Rotation	180°

INSULATION GAPS

Upper Boom Insulation Gap	108" (2.7m)
Lower Boom Insulation Gap	24" (.61m)

VEHICLE REQUIREMENTS

Cab to Axle (minimum)	161.5" (4.1m)
-----------------------	---------------

NOTE:

1. Specifications may vary without prior notification.
2. Required GVWR can vary significantly with chassis, lift mounting location, service body, accessories, and desired payload.



P.O. Box 20368
Waco, TX 76702-0368
254.399.2100
Fax: 254.399.2651
1.800.825.1085
www.timemfg.com