



徐工徐工 助您成功
XCMG FOR YOUR SUCCESS



XMR30S/40S 轻型压实设备

LIGHT COMPACTIION EQUIPMENT

XMR30S/40S

轻型压实设备

产品简介 / Introduction



XMR30S/40S 振动压路机，作业效率高，应用广泛，适用于道路、机场、港口、堤坝、房屋基础的建设和养护。该机体积小、机动性强，在修建体育场、公园、人行道、停车场、沟槽等市政工程中更是必不可少。

采用铰接式车架、转向灵活，稳定性好。

采用液压传动、液压振动和转向，可靠性高。

前后轮均配有刮泥和洒水装置。

施工时可清楚看到钢轮两侧边缘，易于完成路边压实作业。

The XMR30S/40S is a highly efficient machine designed for a wide range of compaction and maintenance work including roads, airfields, seaports, dams and housing foundations. The compact design and high mobility also make the machine indispensable to municipal construction work such as stadiums, parks, pedestrians, parking area, trenches, etc.

Articulated frame features flexible steering for great stability.

Hydraulic transmission, hydraulic vibration and steering combine to offer unsurpassed reliability.

Both front and rear drums are equipped with scrapers and sprinkler devices.

Excellent drum edge visibility during operation allows for easy compaction of road curbs.

主要技术参数 / Main Specifications

车型	Model	单位 Unit	XMR30S	XMR40
工作质量	operating weight	kg	3000	4000
静线载荷 (前/后)	static linear load(front/rear)	N/cm	116/110	154/154
工作速度	speed	km/h	0-10	0-10
理论爬坡能力	gradeability in theory	%	30	30
最小转弯半径(内/外)	min. turning radius (L/R)	mm	2800/4000	2900/4200
最小离地间隙	min. ground clearance	mm	320	240
轴距	wheel base	mm	1800	1900
转向角	steering angle	±°	30	30
摇摆角	swing angle	±°	10	10
振动频率	vibration frequency	Hz	52	60
振动系统最高压力	vibrating system-max. pressure	Mpa	18	18
转向系统最高压力	steering system-max. pressure	Mpa	16	16
名义振幅	nominal amplitude	mm	0.4	0.4
激振力	centrifugal force	kN	27	40
压实宽度	compacting width	mm	1200	1300
压轮直径	drum diameter	mm	750	800
发动机型号	engine model		Detuz F2L2011	Detuz F3L2011
发动机额定转数	rated engine speed	r/min	2600	2600
发动机额定功率	rated engine power	kw	22	33.9
外形尺寸 (长/宽/高)	overall dimensions(length/width/height)	mm	2733/1272/2706	2865/1405/2937
发动机油耗	rated oil wear	g/kW.h	220	218
液压邮箱容积	hydraulic tank capacity	L	55	67
燃油箱容积	fuel tank capacity	L	80	80
洒水箱容积	water tank capacity	L	150	170

本产品随技术进步将不断改进，如有修改，恕不另行通知。样本图片与实物不符的，以实物为准。
Under our policy of continuous product development and improvement, we reserve the right to change specifications and design without prior notice.

徐工集团工程机械股份有限公司道路机械事业部
ROAD MACHINERY BUSINESS UNIT XCMG CONSTRUCTION MACHINERY CO.,LTD.

2013年一版一次印刷

地址: 江苏省徐州经济技术开发区桃山路1号 邮编: 221004
产品销售: 电话/86 0516 87928888 87938000 87738126 传真/86 0516 87738107
售后服务: 养护机械 电话/86051687738006 压路机 电话Tel/86 0516 85751114 平地机 电话Tel/86 0516 87738101
摊铺机 电话Tel/86 0516 87938756 传真Fax/86 0516 85857433
备件销售: 电话/86 0516 87938867 传真/86 0516 83363922
电子邮件: sales@xcmg.com
网址: http://www.xcmg.com

全国统一客服热线
400-110-9999